


# Cartesian Coordinates, Points, and Transformations

CIS - 600.455/655


Russell Taylor




1




3




4




5




6




7




8



9




10




11


**But: We must find  $F_{CT}$  ... Let's review some math**




### Coordinate Frame Transformation

$$F = [R, p]$$







14



15




16




17







18



19



20



21

## Composition

Assume  $F_1 = [R_1, \vec{p}_1]$ ,  $F_2 = [R_2, \vec{p}_2]$

Then

$$\begin{aligned}
 F_1 \bullet F_2 \bullet \vec{b} &= F_1 \bullet (F_2 \bullet \vec{b}) \\
 &= F_1 \bullet (R_2 \bullet \vec{b} + \vec{p}_2) \\
 &= [R_1, \vec{p}_1] \bullet (R_2 \bullet \vec{b} + \vec{p}_2) \\
 &= R_1 \bullet (R_2 \bullet \vec{b} + \vec{p}_2) + \vec{p}_1 \\
 &= R_1 \bullet R_2 \bullet \vec{b} + R_1 \bullet \vec{p}_2 + \vec{p}_1 \\
 &= [R_1 \bullet R_2, R_1 \bullet \vec{p}_2 + \vec{p}_1] \bullet \vec{b}
 \end{aligned}$$

So

$$\begin{aligned}
 F_1 \bullet F_2 &= [R_1, \vec{p}_1] \bullet [R_2, \vec{p}_2] \\
 &= [R_1 \bullet R_2, R_1 \bullet \vec{p}_2 + \vec{p}_1]
 \end{aligned}$$

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



22

## Vectors


$$\vec{v}_{col} = \begin{bmatrix} v_x \\ v_y \\ v_z \end{bmatrix}$$

$$\vec{v}_{row} = \begin{bmatrix} v_x & v_y & v_z \end{bmatrix}$$

$$\text{length: } \|\vec{v}\| = \sqrt{v_x^2 + v_y^2 + v_z^2}$$

$$\text{dot product: } a = \vec{v} \cdot \vec{w} = (v_x w_x + v_y w_y + v_z w_z) = \|\vec{v}\| \|\vec{w}\| \cos \theta$$

$$\text{cross product: } \vec{u} = \vec{v} \times \vec{w} = \begin{bmatrix} v_y w_z - v_z w_y \\ v_z w_x - v_x w_z \\ v_x w_y - v_y w_x \end{bmatrix}, \|\vec{u}\| = \|\vec{v}\| \|\vec{w}\| \sin \theta$$



Slide acknowledgment: Sarah Graham and Andy Bzostek

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



23

## Matrix representation of cross product operator

Define

$$\hat{\mathbf{a}} \triangleq skew(\vec{\mathbf{a}}) \triangleq \begin{bmatrix} 0 & -a_z & a_y \\ a_z & 0 & -a_x \\ -a_y & a_x & 0 \end{bmatrix}$$

Then

$$\vec{\mathbf{a}} \times \vec{\mathbf{v}} = skew(\vec{\mathbf{a}}) \bullet \vec{\mathbf{v}}$$



## Rotations: Some Notation

$Rot(\vec{\mathbf{a}}, \alpha)$  = Rotation by angle  $\alpha$  about axis  $\vec{\mathbf{a}}$

$\mathbf{R}_{\vec{\mathbf{a}}}(\alpha)$  = Rotation by angle  $\alpha$  about axis  $\vec{\mathbf{a}}$

$$\mathbf{R}(\vec{\mathbf{a}}) = Rot(\vec{\mathbf{a}}, \|\vec{\mathbf{a}}\|)$$

$$\mathbf{R}_{xyz}(\alpha, \beta, \gamma) = \mathbf{R}(\vec{\mathbf{x}}, \alpha) \bullet \mathbf{R}(\vec{\mathbf{y}}, \beta) \bullet \mathbf{R}(\vec{\mathbf{z}}, \gamma)$$

$$\mathbf{R}_{zyz}(\alpha, \beta, \gamma) = \mathbf{R}(\vec{\mathbf{z}}, \alpha) \bullet \mathbf{R}(\vec{\mathbf{y}}, \beta) \bullet \mathbf{R}(\vec{\mathbf{z}}, \gamma)$$



## Rotations: A few useful facts

$$Rot(s\vec{a}, \alpha) \bullet \vec{a} = \vec{a} \quad \text{and} \quad \|Rot(\vec{a}, \alpha) \bullet \vec{b}\| = \|\vec{b}\|$$

$$Rot(\vec{a}, \alpha) = Rot(\hat{\mathbf{a}}, \alpha) \quad \text{where} \quad \hat{\mathbf{a}} = \frac{\vec{a}}{\|\vec{a}\|}$$

NOTE: Unless otherwise stated, we will usually assume that  $\vec{a}$  in  $Rot(\vec{a}, \theta)$  is a unit vector. I.e.,  $\|\vec{a}\|=1$ .

$$Rot(\vec{a}, \alpha) \bullet Rot(\vec{a}, \beta) = Rot(\vec{a}, \alpha + \beta)$$

$$Rot(\vec{a}, \alpha)^{-1} = Rot(\vec{a}, -\alpha)$$

$$Rot(\vec{a}, 0) \bullet \vec{b} = \vec{b} \quad \text{i.e.,} \quad Rot(\vec{a}, 0) = \mathbf{I}_{Rot} = \text{the identity rotation}$$

$$Rot(\hat{\mathbf{a}}, \alpha) \bullet \vec{b} = (\hat{\mathbf{a}} \bullet \vec{b})\hat{\mathbf{a}} + Rot(\hat{\mathbf{a}}, \alpha) \bullet (\vec{b} - (\hat{\mathbf{a}} \bullet \vec{b})\hat{\mathbf{a}})$$

$$Rot(\hat{\mathbf{a}}, \alpha) \bullet Rot(\hat{\mathbf{b}}, \beta) = Rot(\hat{\mathbf{b}}, \beta) \bullet Rot(Rot(\hat{\mathbf{b}}, -\beta) \bullet \hat{\mathbf{a}}, \alpha)$$

$$Rot(\hat{\mathbf{a}}, \alpha) \bullet \mathbf{R}_\beta = \mathbf{R}_\beta \bullet Rot(\mathbf{R}_\beta^{-1} \bullet \hat{\mathbf{a}}, \alpha)$$

$$\mathbf{R}_\alpha \bullet Rot(\hat{\mathbf{b}}, \beta) = Rot(\mathbf{R}_\alpha \bullet \hat{\mathbf{b}}, \beta) \bullet \mathbf{R}_\alpha$$

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



28

## Rotations: more facts

If  $\vec{v} = [v_x, v_y, v_z]^T$  then a rotation  $\mathbf{R} \bullet \vec{v}$  may be described in terms of the effects of  $\mathbf{R}$  on orthogonal unit vectors,  $\vec{e}_x = [1, 0, 0]^T$ ,  $\vec{e}_y = [0, 1, 0]^T$ ,  $\vec{e}_z = [0, 0, 1]^T$

$$\mathbf{R} \bullet \vec{v} = v_x \vec{r}_x + v_y \vec{r}_y + v_z \vec{r}_z$$

where

$$\vec{r}_x = \mathbf{R} \bullet \vec{e}_x$$

$$\vec{r}_y = \mathbf{R} \bullet \vec{e}_y$$

$$\vec{r}_z = \mathbf{R} \bullet \vec{e}_z$$

Note that rotation doesn't affect inner products

$$(\mathbf{R} \bullet \vec{b}) \bullet (\mathbf{R} \bullet \vec{c}) = \vec{b} \bullet \vec{c}$$

or lengths of vectors

$$\|\mathbf{R} \bullet \vec{v}\| = \|\vec{v}\|$$

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics




29

## Rotations in the plane

$$\mathbf{R} \cdot \begin{bmatrix} x \\ y \end{bmatrix} = \begin{bmatrix} x \cos \theta - y \sin \theta \\ x \sin \theta + y \cos \theta \end{bmatrix}$$

$$= \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix} \cdot \begin{bmatrix} x \\ y \end{bmatrix}$$



Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics




30

## Rotations in the plane

$$\mathbf{R} \cdot \begin{bmatrix} \bar{\mathbf{e}}_x & \bar{\mathbf{e}}_y \end{bmatrix} = \begin{bmatrix} \cos \theta & -\sin \theta \\ \sin \theta & \cos \theta \end{bmatrix} \cdot \begin{bmatrix} 1 & 0 \\ 0 & 1 \end{bmatrix}$$

$$= \begin{bmatrix} \mathbf{R} \cdot \bar{\mathbf{e}}_x & \mathbf{R} \cdot \bar{\mathbf{e}}_y \end{bmatrix}$$

$$= \begin{bmatrix} \bar{\mathbf{r}}_x & \bar{\mathbf{r}}_y \end{bmatrix}$$



Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



31

### 3D Rotation Matrices

$$\mathbf{R} \bullet [\vec{e}_x \quad \vec{e}_y \quad \vec{e}_z] = [\mathbf{R} \bullet \vec{e}_x \quad \mathbf{R} \bullet \vec{e}_y \quad \mathbf{R} \bullet \vec{e}_z]$$

$$= [\vec{r}_x \quad \vec{r}_y \quad \vec{r}_z]$$

$$\mathbf{R}^T \bullet \mathbf{R} = \begin{bmatrix} \hat{\mathbf{r}}_x^T \\ \hat{\mathbf{r}}_y^T \\ \hat{\mathbf{r}}_z^T \end{bmatrix} \bullet [\vec{r}_x \quad \vec{r}_y \quad \vec{r}_z]$$

$$= \begin{bmatrix} \vec{r}_x^T \bullet \vec{r}_x & \vec{r}_x^T \bullet \vec{r}_y & \vec{r}_x^T \bullet \vec{r}_z \\ \vec{r}_y^T \bullet \vec{r}_x & \vec{r}_y^T \bullet \vec{r}_y & \vec{r}_y^T \bullet \vec{r}_z \\ \vec{r}_z^T \bullet \vec{r}_x & \vec{r}_z^T \bullet \vec{r}_y & \vec{r}_z^T \bullet \vec{r}_z \end{bmatrix} = \begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \\ 0 & 0 & 1 \end{bmatrix}$$



### Properties of Rotation Matrices

Inverse of a Rotation Matrix equals its transpose:

$$\mathbf{R}^{-1} = \mathbf{R}^T$$

$$\mathbf{R}^T \mathbf{R} = \mathbf{R} \mathbf{R}^T = \mathbf{I}$$

The Determinant of a Rotation matrix is equal to +1:

$$\det(\mathbf{R}) = +1$$

Any Rotation can be described by consecutive rotations about the three primary axes, x, y, and z:

$$\mathbf{R} = \mathbf{R}_{z,\theta} \mathbf{R}_{y,\phi} \mathbf{R}_{x,\psi}$$



# Canonical 3D Rotation Matrices

Note: Right-Handed Coordinate System

$$\mathbf{R}_x(\theta) = Rot(\bar{x}, \theta) = \begin{bmatrix} 1 & 0 & 0 \\ 0 & \cos(\theta) & -\sin(\theta) \\ 0 & \sin(\theta) & \cos(\theta) \end{bmatrix}$$

$$\mathbf{R}_y(\theta) = Rot(\bar{y}, \theta) = \begin{bmatrix} \cos(\theta) & 0 & \sin(\theta) \\ 0 & 1 & 0 \\ -\sin(\theta) & 0 & \cos(\theta) \end{bmatrix}$$

$$\mathbf{R}_z(\theta) = Rot(\bar{z}, \theta) = \begin{bmatrix} \cos(\theta) & -\sin(\theta) & 0 \\ \sin(\theta) & \cos(\theta) & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics




34

## Axis-angle Representations of Rotations

### Rodrigues' Formula (1840)\*

Rotation of a vector  $\bar{b}$  by angle  $\alpha$  about axis  $\bar{a}$   
(Assumes that  $\bar{a}$  is a unit vector,  $\|\bar{a}\| = 1$ )



$$\begin{aligned} \bar{c} &= Rot(\bar{a}, \alpha) \cdot \bar{b} \\ &= \bar{b} \cos \alpha + \bar{a} \times \bar{b} \sin \alpha + \bar{a}(\bar{a} \cdot \bar{b})(1 - \cos \alpha) \end{aligned}$$

In matrix form this is  $\bar{c} = \mathbf{R} \cdot \bar{b}$  where

$$\mathbf{R} = (\cos \alpha) \mathbf{I} + (\sin \alpha) skew(\bar{a}) + (1 - \cos \alpha) \bar{a} \cdot \bar{a}^T$$

\* Olinde Rodrigues, "Des lois géométriques qui régissent les déplacements d'un système solide dans l'espace, et de la variation des coordonnées provenant de ces déplacements considérés indépendants des causes qui peuvent les produire", *Journal de Mathématiques Pures et Appliquées* 5 (1840), 380–440. ([http://sites.mathdoc.fr/JMPA/PDF/JMPA\\_1840\\_1\\_5\\_A39\\_0.pdf](http://sites.mathdoc.fr/JMPA/PDF/JMPA_1840_1_5_A39_0.pdf))

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



35



## Exponential representation

Consider a rotation about axis  $\bar{\mathbf{n}}$  by angle  $\theta$ . Then

$$e^{\text{skew}(\bar{\mathbf{n}})\theta} = \mathbf{I} + \theta \text{skew}(\bar{\mathbf{n}}) + \frac{\theta^2}{2!} \text{skew}(\bar{\mathbf{n}})^2 + \dots$$

By doing some manipulation, you can show

$$\begin{aligned} \text{Rot}(\bar{\mathbf{n}}, \theta) &= e^{\text{skew}(\bar{\mathbf{n}})\theta} \\ &= \mathbf{I} + \text{skew}(\bar{\mathbf{n}})\sin\theta + \text{skew}(\bar{\mathbf{n}})^2(1 - \cos\theta) \\ &= \mathbf{I} + \text{skew}(\bar{\mathbf{n}})\sin\theta + (\bar{\mathbf{n}} \bullet \bar{\mathbf{n}}^T - \mathbf{I})(1 - \cos\theta) \\ &= \mathbf{I}\cos\theta + \text{skew}(\bar{\mathbf{n}})\sin\theta + \bar{\mathbf{n}} \bullet \bar{\mathbf{n}}^T(1 - \cos\theta) \end{aligned}$$

which is just Rodrigues' formula.

Note that for small  $\theta$ , this reduces to

$$\text{Rot}(\bar{\mathbf{n}}, \theta) \approx \mathbf{I} + \text{skew}(\theta\bar{\mathbf{n}})$$



## Cayley Transform Representation

Consider the rotation  $\text{Rot}(\bar{\mathbf{n}}, \theta)$  and define

$$\bar{\mathbf{a}} = \left( \tan \frac{\theta}{2} \right) \bar{\mathbf{n}}$$

$$\mathbf{A} = \text{skew}(\bar{\mathbf{a}})$$

Then,

$$\mathbf{R} = (\mathbf{I} - \mathbf{A})^{-1}(\mathbf{I} + \mathbf{A}) = (\mathbf{I} + \mathbf{A})(\mathbf{I} - \mathbf{A})^{-1}$$

gives the rotation matrix corresponding to  $\text{Rot}(\bar{\mathbf{n}}, \theta)$ . Similarly, given  $\mathbf{R}$ ,

$$\mathbf{A} = (\mathbf{R} - \mathbf{I})(\mathbf{I} + \mathbf{R})^{-1}$$

gives the elements of  $\text{skew}(\bar{\mathbf{a}})$  and hence for  $\bar{\mathbf{a}}$ .

**Note:** The above relations require that  $\theta \neq \pm\pi$ .



## Note on the difference between two rotations

One often wants to consider the "difference" between two rotations

$$\mathbf{R}_{12} = \mathbf{R}_1^{-1} \cdot \mathbf{R}_2$$

In these cases, it is useful to consider an axis-angle representation

$$\mathbf{R}_{12} = \text{Rot}(\bar{\mathbf{n}}_{12}, \theta_{12})$$

Given  $\mathbf{R}_{12}$ , there are several ways to extract  $\bar{\mathbf{n}}_{12}$  and  $\theta_{12}$ . For example, you can use the Cayley formula to compute  $\bar{\mathbf{a}}_{12} = \tan(\theta_{12} / 2) \bar{\mathbf{n}}_{12}$  from

$$\text{sk}(\bar{\mathbf{a}}_{12}) = (\mathbf{R}_{12} - \mathbf{I})(\mathbf{I} + \mathbf{R}_{12})^{-1}$$

and then

$$\theta_{12} = 2 \arctan(\|\bar{\mathbf{a}}_{12}\|) \quad \text{and} \quad \bar{\mathbf{n}}_{12} = \bar{\mathbf{a}}_{12} / \|\bar{\mathbf{a}}_{12}\|$$

Also, if the rotations are very close to each other so that  $\theta_{12}$  is small, then

$$\mathbf{R}_{12} \approx \mathbf{I} + \text{sk}(\bar{\alpha}_{12})$$

So

$$\theta_{12} \approx \|\bar{\alpha}_{12}\| \quad \text{and} \quad \bar{\mathbf{n}}_{12} \approx \bar{\alpha}_{12} / \theta_{12}$$

This last relationship is very useful in reporting things like registration error since the elements  $\bar{\alpha}_{12}$  are small rotations about the x,y,z axes



## Homogeneous Coordinates

- Widely used in graphics, geometric calculations
- Represent 3D vector as 4D quantity
- For our current purposes, we will keep the "scale"  $s = 1$

$$\vec{\mathbf{V}} \equiv \begin{bmatrix} xS \\ yS \\ zS \\ S \end{bmatrix} \cong \begin{bmatrix} x \\ y \\ z \\ 1 \end{bmatrix}$$



## Representing Frame Transformations as Matrices

$$\mathbf{v} + \mathbf{p} \rightarrow \begin{bmatrix} 1 & 0 & 0 & \mathbf{p}_x \\ 0 & 1 & 0 & \mathbf{p}_y \\ 0 & 0 & 1 & \mathbf{p}_z \\ 0 & 0 & 0 & 1 \end{bmatrix} \begin{bmatrix} \mathbf{v}_x \\ \mathbf{v}_y \\ \mathbf{v}_z \\ 1 \end{bmatrix} = [\mathbf{I}, \bar{\mathbf{p}}] \bullet \mathbf{v}$$

$$\mathbf{R} \bullet \mathbf{v} \rightarrow \begin{bmatrix} \mathbf{R} & \mathbf{0} \\ \mathbf{0} & 1 \end{bmatrix} \begin{bmatrix} \mathbf{v} \\ 1 \end{bmatrix}$$

$$\mathbf{P} \bullet \mathbf{R} \rightarrow \begin{bmatrix} \mathbf{I} & \mathbf{p} \\ \mathbf{0} & 1 \end{bmatrix} \bullet \begin{bmatrix} \mathbf{R} & \mathbf{0} \\ \mathbf{0} & 1 \end{bmatrix} = \begin{bmatrix} \mathbf{R} & \mathbf{p} \\ \mathbf{0} & 1 \end{bmatrix} = [\mathbf{R}, \mathbf{p}] = \mathbf{F}$$


$$\mathbf{F} \bullet \mathbf{v} \rightarrow \begin{bmatrix} \mathbf{R} & \mathbf{p} \\ \mathbf{0} & 1 \end{bmatrix} \begin{bmatrix} \mathbf{v} \\ 1 \end{bmatrix} = \begin{bmatrix} (\mathbf{R} \bullet \mathbf{v}) + \mathbf{p} \\ 1 \end{bmatrix}$$

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



41




Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics




42







47




48




49



50



51



52

## Frame transformation from 3 point pairs

$$\vec{v}_k = \mathbf{F}_{rC} \vec{b}_k = \mathbf{R}_{rC} \vec{b}_k + \vec{p}_{rC}$$

Define

$$\vec{v}_m = \frac{1}{3} \sum_1^3 \vec{v}_k \quad \vec{b}_m = \frac{1}{3} \sum_1^3 \vec{b}_k$$

$$\vec{u}_k = \vec{v}_k - \vec{v}_m \quad \vec{a}_k = \vec{b}_k - \vec{b}_m$$

$$\mathbf{F}_{rC} \vec{a}_k = \mathbf{R}_{rC} \vec{a}_k + \vec{p}_{rC}$$



$$\mathbf{R}_{rC} \vec{a}_k + \vec{p}_{rC} = \mathbf{R}_{rC} (\vec{b}_k - \vec{b}_m) + \vec{p}_{rC}$$

$$\mathbf{R}_{rC} \vec{a}_k = \mathbf{R}_{rC} \vec{b}_k + \vec{p}_{rC} - \mathbf{R}_{rC} \vec{b}_m - \vec{p}_{rC}$$

$$\mathbf{R}_{rC} \vec{a}_k = \vec{v}_k - \vec{v}_m = \vec{u}_k$$

$$\vec{p}_{rC} = \vec{v}_m - \mathbf{R}_{rC} \vec{b}_m$$

**Solve  
These!!**



Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



53

## Rotation from multiple vector pairs

Given a system  $\mathbf{R}\vec{a}_k = \vec{u}_k$  for  $k=1, \dots, n$  the problem is to estimate  $\mathbf{R}$ . This will require at least three such point pairs. Later in the course we will cover some good ways to solve this system. Here is a not-so-good way that will produce roughly correct answers:

Step 1: Form matrices  $\mathbf{U} = [\vec{u}_1 \ \dots \ \vec{u}_n]$  and  $\mathbf{A} = [\vec{a}_1 \ \dots \ \vec{a}_n]$

Step 2: Solve the system  $\mathbf{R}\mathbf{A} = \mathbf{U}$  for  $\mathbf{R}$ . E.g., by  $\mathbf{R} = \mathbf{U}\mathbf{A}^{-1}$

Step 3: Renormalize  $\mathbf{R}$  to guarantee  $\mathbf{R}^T\mathbf{R} = \mathbf{I}$ .

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



54



## Renormalizing Rotation Matrix

Given "rotation" matrix  $\mathbf{R} = [\vec{r}_x \mid \vec{r}_y \mid \vec{r}_z]$ , modify it so  $\mathbf{R}^T \mathbf{R} = \mathbf{I}$ .

Step 1:  $\vec{a} = \vec{r}_y \times \vec{r}_z$

Step 2:  $\vec{b} = \vec{r}_z \times \vec{a}$


Step 3:  $\mathbf{R}_{normalized} = \left[ \begin{array}{c|c|c} \frac{\vec{a}}{\|\vec{a}\|} & \frac{\vec{b}}{\|\vec{b}\|} & \frac{\vec{r}_z}{\|\vec{r}_z\|} \end{array} \right]$



55

## Calibrating a pointer


But what is  $\mathbf{b}_{tip}$ ??



56

## Calibrating a pointer

$$\begin{aligned}\vec{\mathbf{b}}_{post} &= \mathbf{F}_k \vec{\mathbf{b}}_{tip} \\ &= \mathbf{R}_k \vec{\mathbf{b}}_{tip} + \vec{\mathbf{p}}_k\end{aligned}$$



Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



57

## Calibrating a pointer

For each measurement  $k$ , we have


$$\vec{\mathbf{b}}_{post} = \mathbf{R}_k \vec{\mathbf{b}}_{tip} + \vec{\mathbf{p}}_k$$

i. e.,

$$\mathbf{R}_k \vec{\mathbf{b}}_{tip} - \vec{\mathbf{b}}_{post} = -\vec{\mathbf{p}}_k$$

Set up a least squares problem

$$\begin{bmatrix} \vdots & \vdots \\ \mathbf{R}_k & -\mathbf{I} \\ \vdots & \vdots \end{bmatrix} \begin{bmatrix} \vec{\mathbf{b}}_{tip} \\ \vec{\mathbf{b}}_{post} \end{bmatrix} \cong \begin{bmatrix} \vdots \\ -\vec{\mathbf{p}}_k \\ \vdots \end{bmatrix}$$



Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



58

### "Registration Transformations"

Given a coordinate system  $F_C$  and another coordinate system  $F_G$  (e.g., a CT scan and a tracked "rigid body" attached to the patient), and points  $\vec{c}_i$  in the coordinate system  $F_C$  and points  $\vec{g}_j$  in the coordinate system  $F_G$ , then the "registration transformation"  $F_{GC}$  between  $F_G$  and  $F_C$  is one in which  $F_{GC}\vec{c}_i = \vec{g}_j$ , if and only if  $\vec{c}_i$  and  $\vec{g}_j$  refer to the same or corresponding points.

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes JHU Laboratory for Computational Sensing and Robotics

59

### Use in surgical navigation

$$F_{BA} = F_{BD} F_{DU} F_{UA}$$

$$F_{BA} = F_{BG} F_{GC} F_{CA}$$

$$F_{BG} F_{GC} F_{CA} = F_{BD} F_{DU} F_{UA}$$

$$F_{CA} = (F_{BG} F_{GC})^{-1} F_{BD} F_{DU} F_{UA}$$

$$F_{GC} = F_{BG}^{-1} F_{BD} F_{DU} F_{UA} F_{CA}^{-1}$$

$$F_{GC} = F_{GD} F_{DU} F_{UA} F_{CA}^{-1}$$

where  $F_{GD} = F_{BG}^{-1} F_{BD}$


If an anatomic structure is identified at pose  $F_{UA}$  in ultrasound image coordinates give the formula for computing the corresponding pose  $F_{CA}$  in CT coordinates

**NOTE:** In cases where there is a reference body (here  $F_G$ ) affixed to the patient, it is sometimes convenient to assume that the navigation software routinely transforms all tracked markers to the coordinate system of  $F_G$  (i.e.,  $F_{Gx} = F_{BG}^{-1} F_{Bx}$ ).

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes JHU Laboratory for Computational Sensing and Robotics

60

## Kinematic Links



$$\mathbf{F}_k = \mathbf{F}_{k-1} \bullet \mathbf{F}_{k-1,k}$$

$$\begin{bmatrix} \mathbf{R}_k, \tilde{\mathbf{p}}_k \end{bmatrix} = \begin{bmatrix} \mathbf{R}_{k-1}, \mathbf{p}_{k-1} \end{bmatrix} \bullet \begin{bmatrix} \mathbf{R}_{k-1,k}, \mathbf{p}_{k-1,k} \end{bmatrix}$$


Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



61

## Kinematic Links



$$\mathbf{F}_k = \mathbf{F}_{k-1} \bullet \mathbf{F}_{k-1,k}$$

$$\begin{bmatrix} \mathbf{R}_k, \tilde{\mathbf{p}}_k \end{bmatrix} = \begin{bmatrix} \mathbf{R}_{k-1}, \mathbf{p}_{k-1} \end{bmatrix} \bullet \begin{bmatrix} \mathbf{R}_{k-1,k}, \mathbf{p}_{k-1,k} \end{bmatrix}$$

$$= \begin{bmatrix} \mathbf{R}_{k-1}, \mathbf{p}_{k-1} \end{bmatrix} \bullet \begin{bmatrix} Rot(\vec{\mathbf{r}}_k, \theta_k), \vec{\mathbf{0}} \end{bmatrix} \bullet \begin{bmatrix} \mathbf{I}, L_k \vec{\mathbf{x}} \end{bmatrix}$$

$$= \begin{bmatrix} \mathbf{R}_{k-1}, \mathbf{p}_{k-1} \end{bmatrix} \bullet \begin{bmatrix} Rot(\vec{\mathbf{r}}_k, \theta_k), L_k Rot(\vec{\mathbf{r}}_k, \theta_k) \end{bmatrix} \bullet \vec{\mathbf{x}}$$

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



62

## Kinematic Chains

$$\mathbf{F}_0 = [\mathbf{I}, \vec{\mathbf{0}}]$$


$$\mathbf{R}_3 = \mathbf{R}_{0,1} \mathbf{R}_{1,2} \mathbf{R}_{2,3} = \text{Rot}(\vec{\mathbf{r}}_1, \theta_1) \text{Rot}(\vec{\mathbf{r}}_2, \theta_2) \text{Rot}(\vec{\mathbf{r}}_3, \theta_3)$$

$$\vec{\mathbf{p}}_3 = \vec{\mathbf{p}}_{0,1} + \mathbf{R}_{0,1} (\vec{\mathbf{p}}_{1,2} + \mathbf{R}_{1,2} \vec{\mathbf{p}}_{2,3})$$

$$= L_1 \text{Rot}(\vec{\mathbf{r}}_1, \theta_1) \vec{\mathbf{x}}$$

$$+ L_2 \text{Rot}(\vec{\mathbf{r}}_1, \theta_1) \text{Rot}(\vec{\mathbf{r}}_2, \theta_2) \vec{\mathbf{x}}$$

$$+ L_3 \text{Rot}(\vec{\mathbf{r}}_1, \theta_1) \text{Rot}(\vec{\mathbf{r}}_2, \theta_2) \text{Rot}(\vec{\mathbf{r}}_3, \theta_3) \vec{\mathbf{x}}$$



Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



63

## Kinematic Chains

$$\text{If } \vec{\mathbf{r}}_1 = \vec{\mathbf{r}}_2 = \vec{\mathbf{r}}_3 = \vec{\mathbf{z}},$$

$$\mathbf{R}_3 = \text{Rot}(\vec{\mathbf{z}}, \theta_1) \text{Rot}(\vec{\mathbf{z}}, \theta_2) \text{Rot}(\vec{\mathbf{z}}, \theta_3)$$

$$= \text{Rot}(\vec{\mathbf{z}}, \theta_1 + \theta_2 + \theta_3)$$

$$\vec{\mathbf{p}}_3 = \vec{\mathbf{p}}_{0,1} + \mathbf{R}_{0,1} (\vec{\mathbf{p}}_{1,2} + \mathbf{R}_{1,2} \vec{\mathbf{p}}_{2,3})$$

$$= L_1 \text{Rot}(\vec{\mathbf{z}}, \theta_1) \vec{\mathbf{x}}$$


$$+ L_2 \text{Rot}(\vec{\mathbf{z}}, \theta_1) \text{Rot}(\vec{\mathbf{z}}, \theta_2) \vec{\mathbf{x}}$$

$$+ L_3 \text{Rot}(\vec{\mathbf{z}}, \theta_1) \text{Rot}(\vec{\mathbf{z}}, \theta_2) \text{Rot}(\vec{\mathbf{z}}, \theta_3) \vec{\mathbf{x}}$$

$$= L_1 \text{Rot}(\vec{\mathbf{z}}, \theta_1) \vec{\mathbf{x}}$$

$$+ L_2 \text{Rot}(\vec{\mathbf{z}}, \theta_1 + \theta_2) \vec{\mathbf{x}}$$

$$+ L_3 \text{Rot}(\vec{\mathbf{z}}, \theta_1 + \theta_2 + \theta_3) \vec{\mathbf{x}}$$



Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics




64

## Kinematic Chains

If  $\bar{\mathbf{r}}_1 = \bar{\mathbf{r}}_2 = \bar{\mathbf{r}}_3 = \bar{\mathbf{z}}$ ,

$$\mathbf{R}_3 = \begin{bmatrix} \cos(\theta_1 + \theta_2 + \theta_3) & -\sin(\theta_1 + \theta_2 + \theta_3) & 0 \\ \sin(\theta_1 + \theta_2 + \theta_3) & \cos(\theta_1 + \theta_2 + \theta_3) & 0 \\ 0 & 0 & 1 \end{bmatrix}$$

$$\bar{\mathbf{p}}_3 = \begin{bmatrix} L_1 \cos(\theta_1) + L_2 \cos(\theta_1 + \theta_2) + L_3 \cos(\theta_1 + \theta_2 + \theta_3) \\ L_1 \sin(\theta_1) + L_2 \sin(\theta_1 + \theta_2) + L_3 \sin(\theta_1 + \theta_2 + \theta_3) \\ 0 \end{bmatrix}$$



Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



65

## “Small” Transformations

- A great deal of CIS is concerned with computing and using geometric information based on imprecise knowledge
- Similarly, one is often concerned with the effects of relatively small rotations and displacements
- Essentially, we will be using fairly straightforward linearizations to model these situations, but a specialized notation is often useful

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



67

## “Small” Frame Transformations

Represent a "small" pose shift consisting of a small rotation  $\Delta\mathbf{R}$  followed by a small displacement  $\Delta\vec{\mathbf{p}}$  as

$$\Delta\mathbf{F} = [\Delta\mathbf{R}, \Delta\vec{\mathbf{p}}]$$

Then

$$\Delta\mathbf{F} \bullet \vec{\mathbf{v}} = \Delta\mathbf{R} \bullet \vec{\mathbf{v}} + \Delta\vec{\mathbf{p}}$$



## Small Rotations

$\Delta\mathbf{R}$  = a small rotation

$\mathbf{R}_{\vec{\mathbf{a}}}(\Delta\alpha)$  = a rotation by a small angle  $\Delta\alpha$  about axis  $\vec{\mathbf{a}}$

$\text{Rot}(\vec{\mathbf{a}}, \|\vec{\mathbf{a}}\|) \bullet \vec{\mathbf{b}} \approx \vec{\mathbf{a}} \times \vec{\mathbf{b}} + \vec{\mathbf{b}}$  for  $\|\vec{\mathbf{a}}\|$  sufficiently small

$\Delta\mathbf{R}(\vec{\mathbf{a}})$  = a rotation that is small enough so that any error introduced by this approximation is negligible

$$\Delta\mathbf{R}(\lambda \vec{\mathbf{a}}) \bullet \Delta\mathbf{R}(\mu \vec{\mathbf{b}}) \cong \Delta\mathbf{R}(\lambda \vec{\mathbf{a}} + \mu \vec{\mathbf{b}}) \quad (\text{Linearity for small rotations})$$

**Exercise:** Work out the linearity proposition by substitution



## Approximations to “Small” Frames

$$\begin{aligned}\Delta\mathbf{F}(\bar{\mathbf{a}}, \Delta\bar{\mathbf{p}}) &\triangleq [\Delta\mathbf{R}(\bar{\mathbf{a}}), \Delta\bar{\mathbf{p}}] \\ \Delta\mathbf{F}(\bar{\mathbf{a}}, \Delta\bar{\mathbf{p}}) \bullet \bar{\mathbf{v}} &= \Delta\mathbf{R}(\bar{\mathbf{a}}) \bullet \bar{\mathbf{v}} + \Delta\bar{\mathbf{p}} \\ &\approx \bar{\mathbf{v}} + \bar{\mathbf{a}} \times \bar{\mathbf{v}} + \Delta\bar{\mathbf{p}}\end{aligned}$$

$$\begin{aligned}\bar{\mathbf{a}} \times \bar{\mathbf{v}} &= \text{skew}(\bar{\mathbf{a}}) \bullet \bar{\mathbf{v}} \\ &= \begin{bmatrix} 0 & -a_z & a_y \\ a_z & 0 & -a_x \\ -a_y & a_x & 0 \end{bmatrix} \bullet \begin{bmatrix} v_x \\ v_y \\ v_z \end{bmatrix} \\ \text{skew}(\bar{\mathbf{a}}) \bullet \bar{\mathbf{a}} &= \bar{\mathbf{a}} \times \bar{\mathbf{a}} = \bar{\mathbf{0}}\end{aligned}$$

$$\begin{aligned}\Delta\mathbf{R}(\bar{\mathbf{a}}) &\approx \mathbf{I} + \text{skew}(\bar{\mathbf{a}}) \\ \Delta\mathbf{R}(\bar{\mathbf{a}})^{-1} &\approx \mathbf{I} - \text{skew}(\bar{\mathbf{a}}) = \mathbf{I} + \text{skew}(-\bar{\mathbf{a}})\end{aligned}$$



## Approximations to “Small” Frames

Notational NOTE:

We often use  $\bar{\alpha}$  to represent a vector of small angles  
and  $\bar{\epsilon}$  to represent a vector of small displacements

In using these approximations, we typically ignore second order terms. I.e.,

$$\bar{\alpha}_A \bar{\alpha}_B \approx \bar{\mathbf{0}}, \bar{\alpha}_A \bar{\epsilon}_B \approx \bar{\mathbf{0}}, \bar{\epsilon}_A \bar{\epsilon}_B \approx \bar{\mathbf{0}}, \text{ etc.}$$





## Errors & sensitivity

Often, we do not have an accurate value for a transformation, so we need to model the error. We model this as a composition of a "nominal" frame and a small displacement

$$\mathbf{F}_{\text{actual}} = \mathbf{F}_{\text{nominal}} \bullet \Delta \mathbf{F}$$

Often, we will use the notation  $\mathbf{F}^*$  for  $\mathbf{F}_{\text{actual}}$  and will just use  $\mathbf{F}$  for  $\mathbf{F}_{\text{nominal}}$ . Thus we may write something like

$$\mathbf{F}^* = \mathbf{F} \bullet \Delta \mathbf{F}$$

or (less often)  $\mathbf{F}^* = \Delta \mathbf{F} \bullet \mathbf{F}$ . We also use  $\vec{\mathbf{v}}^* = \vec{\mathbf{v}} + \Delta \vec{\mathbf{v}}$ , etc.

Thus, if we use the former form (error on the right), and

have nominal relationship  $\vec{\mathbf{v}} = \mathbf{F} \bullet \vec{\mathbf{b}}$ , we get

$$\begin{aligned} \vec{\mathbf{v}}^* &= \mathbf{F}^* \bullet \vec{\mathbf{b}}^* \\ &= \mathbf{F} \bullet \Delta \mathbf{F} \bullet (\vec{\mathbf{b}} + \Delta \vec{\mathbf{b}}) = \mathbf{F} \bullet (\Delta \mathbf{R} \bullet \vec{\mathbf{b}} + \Delta \mathbf{R} \bullet \Delta \vec{\mathbf{b}} + \Delta \vec{\mathbf{p}}) \\ &\approx \mathbf{R} \bullet ((\mathbf{I} + sk(\vec{\alpha})) \bullet (\vec{\mathbf{b}} + \Delta \vec{\mathbf{b}}) + \Delta \vec{\mathbf{p}}) + \vec{\mathbf{p}} = \mathbf{R} \bullet (\vec{\mathbf{b}} + \vec{\alpha} \times \vec{\mathbf{b}} + \Delta \vec{\mathbf{b}} + \Delta \vec{\mathbf{p}}) + \vec{\mathbf{p}} \\ &\approx \mathbf{R} \bullet (\vec{\alpha} \times \vec{\mathbf{b}} + \Delta \vec{\mathbf{b}} + \Delta \vec{\mathbf{p}}) + \mathbf{R} \bullet \vec{\mathbf{b}} + \vec{\mathbf{p}} = \mathbf{R} \bullet (\vec{\alpha} \times \vec{\mathbf{b}} + \Delta \vec{\mathbf{b}} + \Delta \vec{\mathbf{p}}) + \vec{\mathbf{v}} \\ \Delta \vec{\mathbf{v}} &\approx \mathbf{R} \bullet (\vec{\alpha} \times \vec{\mathbf{b}} + \Delta \vec{\mathbf{b}} + \Delta \vec{\mathbf{p}}) \end{aligned}$$


Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



72

## "Small Errors"



Suppose that there is a small systematic error in the tracking system so that

$$\mathbf{F}_{Bx}^* = \Delta \mathbf{F}_{Bx}$$

for  $\mathbf{F}_{BG}$ ,  $\mathbf{F}_{BD}$ ,  $\mathbf{F}_{BE}$ . How does this affect the calculation of  $\mathbf{F}_{GH}$ ?

$$\begin{aligned} \mathbf{F}_{GH}^* &= (\mathbf{F}_{BG}^*)^{-1} \mathbf{F}_{BE}^* \mathbf{F}_{EH} \\ \mathbf{F}_{GH} \Delta \mathbf{F}_{GH} &= (\Delta \mathbf{F}_{Bx} \mathbf{F}_{BG})^{-1} \Delta \mathbf{F}_{Bx} \mathbf{F}_{BE} \mathbf{F}_{EH} \\ \Delta \mathbf{F}_{GH} &= \mathbf{F}_{GH}^{-1} (\Delta \mathbf{F}_{Bx} \mathbf{F}_{BG})^{-1} \Delta \mathbf{F}_{Bx} \mathbf{F}_{BE} \mathbf{F}_{EH} \\ &= \mathbf{F}_{GH}^{-1} \mathbf{F}_{BG}^{-1} \Delta \mathbf{F}_{Bx}^{-1} \Delta \mathbf{F}_{Bx} \mathbf{F}_{BE} \mathbf{F}_{EH} \\ &= \mathbf{F}_{GH}^{-1} \mathbf{F}_{BG}^{-1} \mathbf{F}_{BE} \mathbf{F}_{EH} = \mathbf{F}_{GH}^{-1} \mathbf{F}_{GH} = \mathbf{I} \end{aligned}$$

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



73

### “Small Errors”

Suppose that there are additional errors in the tracking of each tracker body so that  $\mathbf{F}_{Bx}^* = \Delta \mathbf{F}_B \mathbf{F}_{Bx} \Delta \mathbf{F}_{Bx}$  for  $\mathbf{F}_{BG}, \mathbf{F}_{BD}, \mathbf{F}_{BE}$ . How does this affect the calculation of  $\mathbf{F}_{GH}$ ?

$$\mathbf{F}_{GH}^* = \mathbf{F}_{GH} \Delta \mathbf{F}_{GH} = (\mathbf{F}_{BG}^*)^{-1} \mathbf{F}_{BE}^* \mathbf{F}_{EH}$$

$$\Delta \mathbf{F}_{GH} = \mathbf{F}_{GH}^{-1} (\Delta \mathbf{F}_B \mathbf{F}_{BG} \Delta \mathbf{F}_{BG})^{-1} (\Delta \mathbf{F}_B \mathbf{F}_{BE} \Delta \mathbf{F}_{BE}) \mathbf{F}_{EH}$$

$$\Delta \mathbf{F}_{GH} = (\mathbf{F}_{BG}^{-1} \mathbf{F}_{BE} \mathbf{F}_{EH})^{-1} \Delta \mathbf{F}_{BG}^{-1} \mathbf{F}_{BG}^{-1} \Delta \mathbf{F}_B^{-1} \Delta \mathbf{F}_B \mathbf{F}_{BE} \Delta \mathbf{F}_{BE} \mathbf{F}_{EH}$$

$$= \mathbf{F}_{EH}^{-1} \mathbf{F}_{BE}^{-1} \mathbf{F}_{BG} \Delta \mathbf{F}_{BG}^{-1} \mathbf{F}_{BG}^{-1} \mathbf{F}_{BE} \Delta \mathbf{F}_{BE} \mathbf{F}_{EH}$$

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes JHU Laboratory for Computational Sensing and Robotics

74


$\mathbf{F} = [\mathbf{R}, \mathbf{p}]$

$\vec{\mathbf{b}}_1$


$\vec{\mathbf{v}}_1$

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes JHU Laboratory for Computational Sensing and Robotics

75



76




77

## Errors & Sensitivity

Suppose that we know nominal values for  $\mathbf{F}$ ,  $\vec{\mathbf{b}}$ , and  $\vec{\mathbf{v}}$  and that

$$[-\varepsilon, -\varepsilon, -\varepsilon]^T \leq \Delta\vec{\mathbf{v}}_1 \leq [\varepsilon, \varepsilon, \varepsilon]^T \quad (\text{i.e., } \|\Delta\vec{\mathbf{v}}_1\|_\infty \leq \varepsilon)$$

What does this tell us about  $\Delta\mathbf{F} = [\Delta\mathbf{R}, \Delta\vec{\mathbf{p}}]$ ?



600.455, Copyright © 1999, 2000 rht+g

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



78

## Errors & Sensitivity

$$\begin{aligned} \vec{\mathbf{v}}^* &= \mathbf{F}^* \bullet \vec{\mathbf{b}}^* \\ &= \mathbf{F} \bullet \Delta\mathbf{F} \bullet (\vec{\mathbf{b}} + \Delta\vec{\mathbf{b}}) \\ &= \mathbf{R} \bullet (\Delta\mathbf{R}(\vec{\alpha}) \bullet (\vec{\mathbf{b}} + \Delta\vec{\mathbf{b}}) + \Delta\vec{\mathbf{p}}) + \vec{\mathbf{p}} \\ &\approx \mathbf{R} \bullet (\vec{\mathbf{b}} + \Delta\vec{\mathbf{b}} + \vec{\alpha} \times \vec{\mathbf{b}} + \vec{\alpha} \times \Delta\vec{\mathbf{b}} + \Delta\vec{\mathbf{p}}) + \vec{\mathbf{p}} \\ &= \mathbf{R} \bullet \vec{\mathbf{b}} + \vec{\mathbf{p}} + \mathbf{R} \bullet (\Delta\vec{\mathbf{b}} + \vec{\alpha} \times \vec{\mathbf{b}} + \vec{\alpha} \times \Delta\vec{\mathbf{b}} + \Delta\vec{\mathbf{p}}) \\ &\approx \vec{\mathbf{v}} + \mathbf{R} \bullet (\Delta\vec{\mathbf{b}} + \vec{\alpha} \times \vec{\mathbf{b}} + \Delta\vec{\mathbf{p}}) \end{aligned}$$

if  $\|\vec{\alpha} \times \Delta\vec{\mathbf{b}}\| \leq \|\vec{\alpha}\| \|\Delta\vec{\mathbf{b}}\|$  is negligible (it usually is)

SO

$$\Delta\vec{\mathbf{v}} = \vec{\mathbf{v}}^* - \vec{\mathbf{v}} \approx \mathbf{R} \bullet (\Delta\vec{\mathbf{b}} + \vec{\alpha} \times \vec{\mathbf{b}} + \Delta\vec{\mathbf{p}}) = \mathbf{R} \bullet \Delta\vec{\mathbf{b}} + \mathbf{R} \bullet \vec{\alpha} \times \vec{\mathbf{b}} + \mathbf{R} \bullet \Delta\vec{\mathbf{p}}$$

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



79

## Digression: “rotation triple product”

Expressions like  $\mathbf{R} \bullet \vec{\mathbf{a}} \times \vec{\mathbf{b}}$  are linear in  $\vec{\mathbf{a}}$ , but are not always convenient to work with. Often we would prefer something like  $\mathbf{M}(\mathbf{R}, \vec{\mathbf{b}}) \bullet \vec{\mathbf{a}}$ .

$$\begin{aligned}\mathbf{R} \bullet \vec{\mathbf{a}} \times \vec{\mathbf{b}} &= -\mathbf{R} \bullet \vec{\mathbf{b}} \times \vec{\mathbf{a}} \\ &= \mathbf{R} \bullet \text{skew}(-\vec{\mathbf{b}}) \bullet \vec{\mathbf{a}} \\ &= \left[ \mathbf{R} \bullet \text{skew}(\vec{\mathbf{b}})^T \right] \bullet \vec{\mathbf{a}}\end{aligned}$$



## Digression: “rotation triple product”

Here are a few more useful facts:

$$\begin{aligned}\mathbf{R} \bullet (\vec{\mathbf{a}} \times \vec{\mathbf{b}}) &= (\mathbf{R} \bullet \vec{\mathbf{a}}) \times (\mathbf{R} \bullet \vec{\mathbf{b}}) \\ \vec{\mathbf{a}} \times (\mathbf{R} \bullet \vec{\mathbf{b}}) &= \mathbf{R} \bullet ((\mathbf{R}^{-1} \bullet \vec{\mathbf{a}}) \times \vec{\mathbf{b}})\end{aligned}$$

Consequently

$$\begin{aligned}\text{skew}(\vec{\mathbf{a}}) \bullet \mathbf{R} &= \mathbf{R} \bullet \text{skew}(\mathbf{R}^{-1} \bullet \vec{\mathbf{a}}) \\ \mathbf{R}^{-1} \text{skew}(\vec{\mathbf{a}}) \bullet \mathbf{R} &= \text{skew}(\mathbf{R}^{-1} \bullet \vec{\mathbf{a}})\end{aligned}$$



## A “standard form” for linearized error expressions

It is often convenient to use identities to rearrange expressions involving small error variables into sums of terms with the general form  $\mathbf{M}_k \bar{\eta}_k$ , where  $\mathbf{M}_k$  involve things known to the computer, and the  $\bar{\eta}_k$  are error variables.

For example,

$$\bar{\gamma} = \mathbf{R} \text{sk}(\bar{\alpha}) \bar{\mathbf{a}} + \text{sk}(\bar{\beta}) \bar{\mathbf{b}}$$

would be rewritten as


$$\bar{\gamma} = -\mathbf{R} \text{sk}(\bar{\mathbf{a}}) \bar{\alpha} - \text{sk}(\bar{\mathbf{b}}) \bar{\beta}$$


or

$$\bar{\gamma} = \mathbf{R} \text{sk}(-\bar{\mathbf{a}}) \bar{\alpha} + \text{sk}(-\bar{\mathbf{b}}) \bar{\beta}$$




## Errors & Sensitivity







84



85




86




87







88




89




90




91



92



93



94

### Errors & Sensitivity

Previous expression was

$$\Delta \vec{v}_1 \approx \mathbf{R} \bullet (\Delta \vec{b}_1 + \vec{\alpha} \times \vec{b} + \Delta \vec{p}_1)$$

Substituting triple product and rearranging gives

$$\Delta \vec{v}_1 \approx \left[ \mathbf{R} \mid \mathbf{R} \mid \mathbf{R} \bullet skew(-\vec{b}) \right] \bullet \begin{bmatrix} \Delta \vec{b}_1 \\ \Delta \vec{p} \\ \vec{\alpha} \end{bmatrix}$$

So

$$\begin{bmatrix} -\epsilon \\ -\epsilon \\ -\epsilon \end{bmatrix} \leq \left[ \mathbf{R} \mid \mathbf{R} \mid \mathbf{R} \bullet skew(-\vec{b}) \right] \begin{bmatrix} \Delta \vec{b}_1 \\ \Delta \vec{p} \\ \vec{\alpha} \end{bmatrix} \leq \begin{bmatrix} \epsilon \\ \epsilon \\ \epsilon \end{bmatrix}$$

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes JHU Laboratory for Computational Sensing and Robotics

95

## Errors & Sensitivity

Now, suppose we know that  $|\Delta \bar{\mathbf{b}}_1| \leq \beta$ , this will give us a system of linear constraints

$$\begin{bmatrix} -\varepsilon \\ -\varepsilon \\ -\varepsilon \\ -\beta \\ -\beta \\ -\beta \end{bmatrix} \leq \begin{bmatrix} \mathbf{R} & \mathbf{R} & \mathbf{R} \bullet \text{skew}(-\bar{\mathbf{b}}) \\ \mathbf{I} & \mathbf{0} & \mathbf{0} \end{bmatrix} \begin{bmatrix} \Delta \bar{\mathbf{b}}_1 \\ \Delta \bar{\mathbf{p}}_1 \\ \bar{\boldsymbol{\alpha}} \end{bmatrix} \leq \begin{bmatrix} \varepsilon \\ \varepsilon \\ \varepsilon \\ \beta \\ \beta \\ \beta \end{bmatrix}$$



## Error from frame composition

Consider  $\mathbf{R}_1^* \mathbf{R}_2^* = \mathbf{R}_3^*$  where  $\mathbf{R}_1^* = \mathbf{R}_1 \Delta \mathbf{R}_1$ ,  $\mathbf{R}_2^* = \mathbf{R}_2 \Delta \mathbf{R}_2$ ,  $\mathbf{R}_3^* = \mathbf{R}_3 \Delta \mathbf{R}_3$  and  $\Delta \mathbf{R}_1 \approx \mathbf{I} + \text{sk}(\bar{\boldsymbol{\alpha}}_1)$ ,  $\Delta \mathbf{R}_2 \approx \mathbf{I} + \text{sk}(\bar{\boldsymbol{\alpha}}_2)$ , estimate  $\Delta \mathbf{R}_3 \approx \mathbf{I} + \text{sk}(\bar{\boldsymbol{\alpha}}_3)$

$$\mathbf{R}_1 \Delta \mathbf{R}_1 \mathbf{R}_2 \Delta \mathbf{R}_2 = \mathbf{R}_1 \mathbf{R}_2 \Delta \mathbf{R}_3$$

$$\mathbf{R}_1 (\mathbf{I} + \text{sk}(\bar{\boldsymbol{\alpha}}_1)) \mathbf{R}_2 (\mathbf{I} + \text{sk}(\bar{\boldsymbol{\alpha}}_2)) \approx \mathbf{R}_1 \mathbf{R}_2 (\mathbf{I} + \text{sk}(\bar{\boldsymbol{\alpha}}_3))$$

$$(\mathbf{R}_1 \mathbf{R}_2)^{-1} \mathbf{R}_1 (\mathbf{I} + \text{sk}(\bar{\boldsymbol{\alpha}}_1)) \mathbf{R}_2 (\mathbf{I} + \text{sk}(\bar{\boldsymbol{\alpha}}_2)) \approx \mathbf{I} + \text{sk}(\bar{\boldsymbol{\alpha}}_3)$$

$$\mathbf{R}_2^{-1} \cancel{\mathbf{R}_1} \mathbf{R}_1 (\mathbf{I} + \text{sk}(\bar{\boldsymbol{\alpha}}_1)) \mathbf{R}_2 (\mathbf{I} + \text{sk}(\bar{\boldsymbol{\alpha}}_2)) \approx \mathbf{I} + \text{sk}(\bar{\boldsymbol{\alpha}}_3)$$

$$\mathbf{I} + \mathbf{R}_2^{-1} \text{sk}(\bar{\boldsymbol{\alpha}}_1) \mathbf{R}_2 + \text{sk}(\bar{\boldsymbol{\alpha}}_2) + \mathbf{R}_2^{-1} \text{sk}(\bar{\boldsymbol{\alpha}}_1) \mathbf{R}_2 \text{sk}(\bar{\boldsymbol{\alpha}}_2) \approx \mathbf{I} + \text{sk}(\bar{\boldsymbol{\alpha}}_3)$$

$$\mathbf{R}_2^{-1} \text{sk}(\bar{\boldsymbol{\alpha}}_1) \mathbf{R}_2 + \text{sk}(\bar{\boldsymbol{\alpha}}_2) \approx \text{sk}(\bar{\boldsymbol{\alpha}}_3)$$

Since  $\mathbf{R}^{-1} \bullet (\bar{\mathbf{a}} \times \mathbf{R} \bar{\mathbf{b}}) = (\mathbf{R}^{-1} \bar{\mathbf{a}}) \times \bar{\mathbf{b}}$  for all  $\mathbf{R}$ ,  $\bar{\mathbf{a}}$ ,  $\bar{\mathbf{b}}$  we get  $\mathbf{R}_2^{-1} \text{sk}(\bar{\boldsymbol{\alpha}}_1) \mathbf{R}_2 = \text{sk}(\mathbf{R}_2^{-1} \bar{\boldsymbol{\alpha}}_1)$

$$\text{sk}(\bar{\boldsymbol{\alpha}}_3) \approx \text{sk}(\mathbf{R}_2^{-1} \bar{\boldsymbol{\alpha}}_1) + \text{sk}(\bar{\boldsymbol{\alpha}}_2) = \text{sk}(\mathbf{R}_2^{-1} \bar{\boldsymbol{\alpha}}_1 + \bar{\boldsymbol{\alpha}}_2)$$

$$\bar{\boldsymbol{\alpha}}_3 \approx \mathbf{R}_2^{-1} \bar{\boldsymbol{\alpha}}_1 + \bar{\boldsymbol{\alpha}}_2$$



## Error from frame composition

Consider  $\mathbf{F}_1^* \mathbf{F}_2^* = \mathbf{F}_3^*$  where  $\mathbf{F}_1^* = \mathbf{F}_1 \Delta \mathbf{F}_1$ ,  $\mathbf{F}_2^* = \mathbf{F}_2 \Delta \mathbf{F}_2$ ,  $\mathbf{F}_3^* = \mathbf{F}_3 \Delta \mathbf{F}_3$   
and  $\Delta \mathbf{F}_1 \approx [\mathbf{I} + \text{sk}(\vec{\alpha}_1), \vec{e}_1]$ ,  $\Delta \mathbf{F}_2 \approx [\mathbf{I} + \text{sk}(\vec{\alpha}_2), \vec{e}_2]$ ,  
estimate  $\Delta \mathbf{F}_3 \approx [\mathbf{I} + \text{sk}(\vec{\alpha}_3), \vec{e}_3]$

From before, we have  $\vec{\alpha}_3 \approx \mathbf{R}_2^{-1} \vec{\alpha}_1 + \vec{\alpha}_2$ . So now we just need  $\vec{e}_3$ .

$$\begin{aligned} \mathbf{F}_3 \Delta \mathbf{F}_3 &= [\mathbf{R}_3 \Delta \mathbf{R}_3, \mathbf{R}_3 \Delta \vec{p}_3 + \vec{p}_3] \\ \vec{p}_3 + \mathbf{R}_3 \Delta \vec{p}_3 &= \mathbf{R}_1 (\Delta \mathbf{R}_1 (\vec{p}_2 + \mathbf{R}_2 \vec{e}_2) + \vec{e}_1) + \vec{p}_1 \\ \vec{p}_3 + \mathbf{R}_3 \vec{e}_3 &\approx \mathbf{R}_1 (\mathbf{I} + \text{sk}(\vec{\alpha}_1)) (\vec{p}_2 + \mathbf{R}_2 \vec{e}_2) + \mathbf{R}_1 \vec{e}_1 + \vec{p}_1 \\ &= \mathbf{R}_1 \vec{p}_2 + \mathbf{R}_1 \mathbf{R}_2 \vec{e}_2 + \mathbf{R}_1 \cdot (\vec{\alpha}_1 \times \vec{p}_2 + \vec{\alpha}_1 \times \mathbf{R}_2 \vec{e}_2) + \vec{p}_1 + \mathbf{R}_1 \vec{e}_1 \\ &= \vec{p}_3 + \mathbf{R}_1 \mathbf{R}_2 \vec{e}_2 + \mathbf{R}_1 \cdot (\vec{\alpha}_1 \times \vec{p}_2 + \vec{\alpha}_1 \times \mathbf{R}_2 \vec{e}_2) + \mathbf{R}_1 \vec{e}_1 \\ \mathbf{R}_3 \vec{e}_3 &\approx \mathbf{R}_1 \mathbf{R}_2 \vec{e}_2 + \mathbf{R}_1 \cdot \vec{\alpha}_1 \times \vec{p}_2 + \mathbf{R}_1 \vec{e}_1 \\ \vec{e}_3 &\approx \mathbf{R}_2^{-1} \mathbf{R}_1^{-1} \mathbf{R}_1 \mathbf{R}_2 \vec{e}_2 + \mathbf{R}_2^{-1} \mathbf{R}_1^{-1} \mathbf{R}_1 \cdot \vec{\alpha}_1 \times \vec{p}_2 + \mathbf{R}_2^{-1} \mathbf{R}_1^{-1} \mathbf{R}_1 \vec{e}_1 \\ &= \vec{e}_2 + \mathbf{R}_2^{-1} \cdot \vec{\alpha}_1 \times \vec{p}_2 + \mathbf{R}_2^{-1} \vec{e}_1 \\ &= \vec{e}_2 - \mathbf{R}_2^{-1} \text{sk}(\vec{p}_2) \vec{\alpha}_1 + \mathbf{R}_2^{-1} \vec{e}_1 \end{aligned}$$



## Inverse of frame transformation with errors

For  $\mathbf{F}^* = \mathbf{F} \Delta \mathbf{F}$ , if we want  $\Delta \mathbf{F}_i$  such that  $\mathbf{F}_i^* = \mathbf{F}_i \Delta \mathbf{F}_i$ , we have

$$\begin{aligned} \mathbf{F}_i &= \mathbf{F}^{-1} = [\mathbf{R}^{-1}, -\mathbf{R}^{-1} \vec{p}] \\ \mathbf{F}_i^* &= \mathbf{F}_i \Delta \mathbf{F}_i = (\mathbf{F} \Delta \mathbf{F})^{-1} = \Delta \mathbf{F}^{-1} \mathbf{F}^{-1} = [\Delta \mathbf{R}^{-1}, -\Delta \mathbf{R}^{-1} \Delta \vec{p}] \cdot [\mathbf{R}^{-1}, -\mathbf{R}^{-1} \vec{p}] \\ \mathbf{F}_i \Delta \mathbf{F}_i &= [\Delta \mathbf{R}^{-1} \mathbf{R}^{-1}, -\Delta \mathbf{R}^{-1} \mathbf{R}^{-1} \vec{p} - \Delta \mathbf{R}^{-1} \Delta \vec{p}] \\ \Delta \mathbf{F}_i &= \mathbf{F}_i^{-1} [\Delta \mathbf{R}^{-1} \mathbf{R}^{-1}, -\Delta \mathbf{R}^{-1} \mathbf{R}^{-1} \vec{p} - \Delta \mathbf{R}^{-1} \Delta \vec{p}] \\ &= (\mathbf{F}^{-1})^{-1} [\Delta \mathbf{R}^{-1} \mathbf{R}^{-1}, -\Delta \mathbf{R}^{-1} \mathbf{R}^{-1} \vec{p} - \Delta \mathbf{R}^{-1} \Delta \vec{p}] \\ &= [\mathbf{R}, \vec{p}] \cdot [\Delta \mathbf{R}^{-1} \mathbf{R}^{-1}, -\Delta \mathbf{R}^{-1} \mathbf{R}^{-1} \vec{p} - \Delta \mathbf{R}^{-1} \Delta \vec{p}] \\ &= [\mathbf{R} \Delta \mathbf{R}^{-1} \mathbf{R}^{-1}, -\mathbf{R} \Delta \mathbf{R}^{-1} \mathbf{R}^{-1} \vec{p} - \mathbf{R} \Delta \mathbf{R}^{-1} \Delta \vec{p} + \vec{p}] \end{aligned}$$



## Inverse of frame transformation with errors

For  $\mathbf{F}^* = \Delta\mathbf{F}\mathbf{F}$ , if we want  $\mathbf{F}_i^* = \Delta\mathbf{F}_i\mathbf{F}_i$ , we have

$$\begin{aligned}\mathbf{F}_i &= \mathbf{F}^{-1} = [\mathbf{R}^{-1}, -\mathbf{R}^{-1}\vec{\mathbf{p}}] \\ \mathbf{F}_i^* &= \Delta\mathbf{F}_i\mathbf{F}_i = (\Delta\mathbf{F}\mathbf{F})^{-1} = \mathbf{F}^{-1}\Delta\mathbf{F}^{-1} = [\mathbf{R}^{-1}, -\mathbf{R}^{-1}\vec{\mathbf{p}}] \cdot [\Delta\mathbf{R}^{-1}, -\Delta\mathbf{R}^{-1}\Delta\vec{\mathbf{p}}] \\ \Delta\mathbf{F}_i\mathbf{F}_i &= [\mathbf{R}^{-1}\Delta\mathbf{R}^{-1}, -\mathbf{R}^{-1}\Delta\mathbf{R}^{-1}\Delta\vec{\mathbf{p}} - \mathbf{R}^{-1}\vec{\mathbf{p}}] \\ \Delta\mathbf{F}_i &= [\mathbf{R}^{-1}\Delta\mathbf{R}^{-1}, -\mathbf{R}^{-1}\Delta\mathbf{R}^{-1}\Delta\vec{\mathbf{p}} - \mathbf{R}^{-1}\vec{\mathbf{p}}] \cdot [\mathbf{R}, \vec{\mathbf{p}}] \\ &= [\mathbf{R}^{-1}\Delta\mathbf{R}^{-1}\mathbf{R}, \mathbf{R}^{-1}\Delta\mathbf{R}^{-1}\vec{\mathbf{p}} - \mathbf{R}^{-1}\Delta\mathbf{R}^{-1}\Delta\vec{\mathbf{p}} - \mathbf{R}^{-1}\vec{\mathbf{p}}]\end{aligned}$$




## Inverse of frame transformation with errors

Suppose we know that  $\Delta\mathbf{R}$  is "small", i.e.,  $\Delta\mathbf{R} \approx \mathbf{I} + sk(\vec{\alpha})$ , and for notational convenience we write  $\Delta\vec{\mathbf{p}} = \vec{\epsilon}$ , we get

$$\begin{aligned}\Delta\mathbf{R}_i &= \mathbf{R}\Delta\mathbf{R}^{-1}\mathbf{R}^{-1} \approx \mathbf{R}(\mathbf{I} + sk(\vec{\alpha}))^{-1}\mathbf{R}^{-1} \\ &\approx \mathbf{R}(\mathbf{I} - sk(\vec{\alpha}))\mathbf{R}^{-1} \\ &= \mathbf{R}\mathbf{R}^{-1} - \mathbf{R}sk(\vec{\alpha})\mathbf{R}^{-1} \\ &= \mathbf{I} - \mathbf{R}sk(\vec{\alpha})\mathbf{R}^{-1} \\ &= \mathbf{I} - sk\left(\left(\mathbf{R}^{-1}\right)^{-1}\vec{\alpha}\right) = \mathbf{I} - sk(\mathbf{R}\vec{\alpha}) \\ \Delta\vec{\mathbf{p}}_i &= -\mathbf{R}\Delta\mathbf{R}^{-1}\mathbf{R}^{-1}\vec{\mathbf{p}} - \mathbf{R}\Delta\mathbf{R}^{-1}\Delta\vec{\mathbf{p}} + \vec{\mathbf{p}} \\ &\approx -\mathbf{R}(\mathbf{I} - sk(\vec{\alpha}))\mathbf{R}^{-1}\vec{\mathbf{p}} - \mathbf{R}(\mathbf{I} - sk(\vec{\alpha}))\vec{\epsilon} + \vec{\mathbf{p}} \\ &= -\vec{\mathbf{p}} + \mathbf{R}sk(\vec{\alpha})\mathbf{R}^{-1}\vec{\mathbf{p}} - \mathbf{R}\vec{\epsilon} + \mathbf{R}sk(\vec{\alpha})\vec{\epsilon} + \vec{\mathbf{p}} \\ &\approx \mathbf{R}sk(\vec{\alpha})\mathbf{R}^{-1}\vec{\mathbf{p}} - \mathbf{R}\vec{\epsilon} = \mathbf{R}(\vec{\alpha} \times \mathbf{R}^{-1}\vec{\mathbf{p}}) - \mathbf{R}\vec{\epsilon} \\ \Delta\vec{\mathbf{p}} &\approx -\mathbf{R}\vec{\epsilon} - \mathbf{R}sk(\mathbf{R}^{-1}\vec{\mathbf{p}})\vec{\alpha}\end{aligned}$$



## Error Propagation in Chains



$$\begin{aligned} \mathbf{F}_k^* &= \mathbf{F}_{k-1}^* \bullet \mathbf{F}_{k-1,k}^* \\ \mathbf{F}_k \Delta \mathbf{F}_k &= \mathbf{F}_{k-1} \Delta \mathbf{F}_{k-1} \mathbf{F}_{k-1,k} \Delta \mathbf{F}_{k-1,k} \\ \Delta \mathbf{F}_k &= (\mathbf{F}_k^{-1} \mathbf{F}_{k-1}) \Delta \mathbf{F}_{k-1} \mathbf{F}_{k-1,k} \Delta \mathbf{F}_{k-1,k} \\ &= (\mathbf{F}_{k-1,k}^{-1} \Delta \mathbf{F}_{k-1} \mathbf{F}_{k-1,k}) \Delta \mathbf{F}_{k-1,k} \end{aligned}$$


Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



105

## Error Propagation in Chains



$$\begin{aligned} \Delta \mathbf{F}_k &= (\mathbf{F}_k^{-1} \mathbf{F}_{k-1}) \Delta \mathbf{F}_{k-1} \mathbf{F}_{k-1,k} \Delta \mathbf{F}_{k-1,k} \\ &= (\mathbf{F}_{k-1,k}^{-1} \Delta \mathbf{F}_{k-1} \mathbf{F}_{k-1,k}) \Delta \mathbf{F}_{k-1,k} \\ \Delta \mathbf{R}_k &= (\mathbf{R}_{k-1,k}^{-1} \Delta \mathbf{R}_{k-1} \mathbf{R}_{k-1,k}) \Delta \mathbf{R}_{k-1,k} \\ &\approx (\mathbf{R}_{k-1,k}^{-1} (\mathbf{I} + \text{skew}(\vec{\alpha}_{k-1})) \mathbf{R}_{k-1,k}) (\mathbf{I} + \text{skew}(\vec{\alpha}_{k-1,k})) \\ &\approx \mathbf{I} + (\mathbf{R}_{k-1,k}^{-1} \text{skew}(\vec{\alpha}_{k-1}) \mathbf{R}_{k-1,k}) + \text{skew}(\vec{\alpha}_{k-1,k}) = \mathbf{I} + \text{skew}(\mathbf{R}_{k-1,k}^{-1} \vec{\alpha}_{k-1} + \vec{\alpha}_{k-1,k}) \end{aligned}$$

Note: This is same as what we could have obtained by substituting in formulas from the "error from frame composition" slides given earlier.

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



106




## Exercise

Suppose that you have

$$\Delta \mathbf{R}_{k-1,k} = \Delta \mathbf{R}(\bar{\mathbf{a}}_k) \cong \mathbf{I} + \text{skew}(\bar{\mathbf{a}}_k)$$

$$\Delta \bar{\mathbf{p}}_{k-1,k} = \bar{\mathbf{e}}_k$$

Work out approximate formulas for  $[\Delta \mathbf{R}_3, \Delta \bar{\mathbf{p}}_3]$  in terms of  $L_k, \bar{\mathbf{r}}_k, \theta_k, \bar{\mathbf{a}}_k$  and  $\bar{\mathbf{e}}_k$ . You should come up with a formula that is linear in  $L_k, \bar{\mathbf{a}}_k$ , and  $\bar{\mathbf{e}}_k$ .



Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics




107

## Exercise

Suppose we want to know error in  $\mathbf{F}_{0,3} = \mathbf{F}_0^{-1} \mathbf{F}_3$

$$\begin{aligned} \mathbf{F}_{0,3} &= \mathbf{F}_0^{-1} \mathbf{F}_{0,1} \mathbf{F}_{1,2} \mathbf{F}_{2,3} \\ \mathbf{F}_{0,3}^* &= \mathbf{F}_0^{-1} \mathbf{F}_{0,1}^* \mathbf{F}_{1,2}^* \mathbf{F}_{2,3}^* \\ \mathbf{F}_{0,3} \Delta \mathbf{F}_{0,3} &= \mathbf{F}_0^{-1} \mathbf{F}_{0,1}^* \mathbf{F}_{1,2}^* \mathbf{F}_{2,3}^* \\ \Delta \mathbf{F}_{0,3} &= \mathbf{F}_{0,3}^{-1} \mathbf{F}_{0,1} \Delta \mathbf{F}_{0,1} \mathbf{F}_{1,2} \Delta \mathbf{F}_{1,2} \mathbf{F}_{2,3} \Delta \mathbf{F}_{2,3} \\ &= \mathbf{F}_{2,3}^{-1} \mathbf{F}_{1,2}^{-1} \mathbf{F}_0^{-1} \mathbf{F}_{0,1} \Delta \mathbf{F}_{0,1} \mathbf{F}_{1,2} \Delta \mathbf{F}_{1,2} \mathbf{F}_{2,3} \Delta \mathbf{F}_{2,3} \\ &= \mathbf{F}_{2,3}^{-1} \mathbf{F}_{1,2}^{-1} \Delta \mathbf{F}_{0,1} \mathbf{F}_{0,1} \mathbf{F}_{1,2} \Delta \mathbf{F}_{1,2} \mathbf{F}_{2,3} \Delta \mathbf{F}_{2,3} \end{aligned}$$

Now substitute and simplify



Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



108

### Another Example

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes JHU Laboratory for Computational Sensing and Robotics

109

### Another Example

$$\begin{aligned} \vec{p}_{Tf} &= F_{TU} \cdot \vec{p}_{Uf} \\ F_{TU} &= F_B \cdot F_{BU} \\ &= [R_B \cdot R_{BU}, R_B \cdot \vec{p}_{BU} + \vec{p}_B] \\ \vec{p}_{Tf} &= R_B \cdot R_{BU} \cdot \vec{p}_{Uf} + R_B \cdot \vec{p}_{BU} + \vec{p}_B \end{aligned}$$

**Also**

$$\begin{aligned} \vec{p}_{Tf} &= F_B \cdot \vec{p}_{Bf} \\ \vec{p}_{Bf} &= F_{BU} \cdot \vec{p}_{Uf} \\ &= R_{BU} \cdot \vec{p}_{Uf} + \vec{p}_{BU} \\ \vec{p}_{Tf} &= R_B \cdot R_{BU} \cdot \vec{p}_{Uf} + R_B \cdot \vec{p}_{BU} + \vec{p}_B \end{aligned}$$

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes JHU Laboratory for Computational Sensing and Robotics


110

## Another Example

Suppose that the track body to US calibration is not perfect

$$\begin{aligned} \mathbf{F}_{BU}^* &= \mathbf{F}_{BU} \Delta \mathbf{F}_{BU} \\ &= [\mathbf{R}_{BU} \Delta \mathbf{R}_{BU}, \mathbf{R}_{BU} \Delta \vec{\mathbf{p}}_{BU} + \vec{\mathbf{p}}_{BU}] \end{aligned}$$

$$\begin{aligned} \vec{\mathbf{p}}_{Bf}^* &= \mathbf{F}_{BU}^* \cdot \vec{\mathbf{p}}_{Uf} \quad \text{i.e.,} \quad \vec{\mathbf{p}}_{Bf} + \Delta \vec{\mathbf{p}}_{Bf} = \mathbf{F}_{BU} \Delta \mathbf{F}_{BU} \vec{\mathbf{p}}_{Uf} \\ \Delta \vec{\mathbf{p}}_{Bf} &= \mathbf{F}_{BU} \Delta \mathbf{F}_{BU} \vec{\mathbf{p}}_{Uf} - \vec{\mathbf{p}}_{Bf} \\ &= \mathbf{F}_{BU} (\Delta \mathbf{R}_{BU} \vec{\mathbf{p}}_{Uf} + \Delta \vec{\mathbf{p}}_{BU}) - (\mathbf{R}_{BU} \vec{\mathbf{p}}_{Uf} + \vec{\mathbf{p}}_{BU}) \\ &= \mathbf{R}_{BU} \Delta \mathbf{R}_{BU} \vec{\mathbf{p}}_{Uf} + \mathbf{R}_{BU} \Delta \vec{\mathbf{p}}_{BU} + \vec{\mathbf{p}}_{BU} - \mathbf{R}_{BU} \vec{\mathbf{p}}_{Uf} - \vec{\mathbf{p}}_{BU} \\ &= \mathbf{R}_{BU} \Delta \mathbf{R}_{BU} \vec{\mathbf{p}}_{Uf} + \mathbf{R}_{BU} \Delta \vec{\mathbf{p}}_{BU} - \mathbf{R}_{BU} \vec{\mathbf{p}}_{Uf} \end{aligned}$$



Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



111

## Another Example

Continuing ...

$$\begin{aligned} \Delta \vec{\mathbf{p}}_{Bf} &= \mathbf{R}_{BU} \Delta \mathbf{R}_{BU} \vec{\mathbf{p}}_{Uf} + \mathbf{R}_{BU} \Delta \vec{\mathbf{p}}_{BU} - \mathbf{R}_{BU} \vec{\mathbf{p}}_{Uf} \\ &\approx \mathbf{R}_{BU} (\mathbf{I} + \text{skew}(\vec{\alpha}_{BU})) \vec{\mathbf{p}}_{Uf} + \mathbf{R}_{BU} \Delta \vec{\mathbf{p}}_{BU} - \mathbf{R}_{BU} \vec{\mathbf{p}}_{Uf} \\ &= \cancel{\mathbf{R}_{BU} \vec{\mathbf{p}}_{Uf}} + \mathbf{R}_{BU} \cdot \vec{\alpha}_{BU} \times \vec{\mathbf{p}}_{Uf} + \mathbf{R}_{BU} \Delta \vec{\mathbf{p}}_{BU} - \cancel{\mathbf{R}_{BU} \vec{\mathbf{p}}_{Uf}} \\ &= \mathbf{R}_{BU} \cdot \vec{\alpha}_{BU} \times \vec{\mathbf{p}}_{Uf} + \mathbf{R}_{BU} \Delta \vec{\mathbf{p}}_{BU} \\ &= -\mathbf{R}_{BU} \cdot \vec{\mathbf{p}}_{Uf} \times \vec{\alpha}_{BU} + \mathbf{R}_{BU} \Delta \vec{\mathbf{p}}_{BU} \\ &= \mathbf{R}_{BU} \text{skew}(-\vec{\mathbf{p}}_{Uf}) \vec{\alpha}_{BU} + \mathbf{R}_{BU} \Delta \vec{\mathbf{p}}_{BU} \end{aligned}$$

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



112

## Another Example

$$\begin{aligned}
 \bar{\mathbf{p}}_{Tf} + \Delta \bar{\mathbf{p}}_{Tf} &= \mathbf{F}_B \Delta \mathbf{F}_B (\bar{\mathbf{p}}_{Bf} + \Delta \bar{\mathbf{p}}_{Bf}) \\
 \Delta \bar{\mathbf{p}}_{Tf} &= \mathbf{F}_B \Delta \mathbf{F}_B (\bar{\mathbf{p}}_{Bf} + \Delta \bar{\mathbf{p}}_{Bf}) - \mathbf{F}_B \bar{\mathbf{p}}_{Bf} \\
 \Delta \mathbf{F}_B (\bar{\mathbf{p}}_{Bf} + \Delta \bar{\mathbf{p}}_{Bf}) &= \Delta \mathbf{R}_B (\bar{\mathbf{p}}_{Bf} + \Delta \bar{\mathbf{p}}_{Bf}) + \Delta \bar{\mathbf{p}}_B \\
 &\approx (\mathbf{I} + \text{skew}(\bar{\boldsymbol{\alpha}}_B)) (\bar{\mathbf{p}}_{Bf} + \Delta \bar{\mathbf{p}}_{Bf}) + \Delta \bar{\mathbf{p}}_B \\
 &= (\bar{\mathbf{p}}_{Bf} + \Delta \bar{\mathbf{p}}_{Bf}) + \bar{\boldsymbol{\alpha}}_B \times \bar{\mathbf{p}}_{Bf} + \cancel{\bar{\boldsymbol{\alpha}}_B \times \Delta \bar{\mathbf{p}}_{Bf}} + \Delta \bar{\mathbf{p}}_B \\
 &\approx \bar{\mathbf{p}}_{Bf} + \Delta \bar{\mathbf{p}}_{Bf} + \bar{\boldsymbol{\alpha}}_B \times \bar{\mathbf{p}}_{Bf} + \Delta \bar{\mathbf{p}}_B \\
 \Delta \bar{\mathbf{p}}_{Tf} &\approx \mathbf{F}_B (\bar{\mathbf{p}}_{Bf} + \Delta \bar{\mathbf{p}}_{Bf} + \bar{\boldsymbol{\alpha}}_B \times \bar{\mathbf{p}}_{Bf} + \Delta \bar{\mathbf{p}}_B) - \mathbf{F}_B \bar{\mathbf{p}}_{Bf} \\
 &= \mathbf{R}_B (\bar{\mathbf{p}}_{Bf} + \Delta \bar{\mathbf{p}}_{Bf} + \bar{\boldsymbol{\alpha}}_B \times \bar{\mathbf{p}}_{Bf} + \Delta \bar{\mathbf{p}}_B) + \bar{\mathbf{p}}_B - (\mathbf{R}_B \bar{\mathbf{p}}_{Bf} + \bar{\mathbf{p}}_B) \\
 &= \mathbf{R}_B (\Delta \bar{\mathbf{p}}_{Bf} + \bar{\boldsymbol{\alpha}}_B \times \bar{\mathbf{p}}_{Bf} + \Delta \bar{\mathbf{p}}_B) \\
 \Delta \bar{\mathbf{p}}_{Bf} &\approx \mathbf{R}_{BU} \text{skew}(-\bar{\mathbf{p}}_{BU}) \bar{\boldsymbol{\alpha}}_{BU} + \mathbf{R}_{BU} \Delta \bar{\mathbf{p}}_{BU}
 \end{aligned}$$

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes JHU Laboratory for Computational Sensing and Robotics



113

## Another Example

$$\begin{aligned}
 \Delta \bar{\mathbf{p}}_{Tf} &\approx \mathbf{R}_B (\Delta \bar{\mathbf{p}}_{Bf} + \bar{\boldsymbol{\alpha}}_B \times \bar{\mathbf{p}}_{Bf} + \Delta \bar{\mathbf{p}}_B) \\
 \Delta \bar{\mathbf{p}}_{Bf} &\approx \mathbf{R}_{BU} \text{skew}(-\bar{\mathbf{p}}_{BU}) \bar{\boldsymbol{\alpha}}_{BU} + \mathbf{R}_{BU} \Delta \bar{\mathbf{p}}_{BU} \\
 \Delta \bar{\mathbf{p}}_{Tf} &\approx \mathbf{R}_B (\mathbf{R}_{BU} \text{skew}(-\bar{\mathbf{p}}_{BU}) \bar{\boldsymbol{\alpha}}_{BU} + \mathbf{R}_{BU} \Delta \bar{\mathbf{p}}_{BU} + \bar{\boldsymbol{\alpha}}_B \times \bar{\mathbf{p}}_{Bf} + \Delta \bar{\mathbf{p}}_B) \\
 &= \begin{pmatrix} \mathbf{R}_B \mathbf{R}_{BU} \text{skew}(-\bar{\mathbf{p}}_{BU}) \bar{\boldsymbol{\alpha}}_{BU} + \mathbf{R}_B \mathbf{R}_{BU} \Delta \bar{\mathbf{p}}_{BU} \\ \mathbf{R}_B \text{skew}(-\bar{\mathbf{p}}_{Bf}) \bar{\boldsymbol{\alpha}}_B + \mathbf{R}_B \Delta \bar{\mathbf{p}}_B \end{pmatrix} \\
 &= \left[ \mathbf{R}_B \mathbf{R}_{BU} \text{skew}(-\bar{\mathbf{p}}_{BU}) \mid \mathbf{R}_B \mathbf{R}_{BU} \mid \mathbf{R}_B \text{skew}(-\bar{\mathbf{p}}_{Bf}) \mid \mathbf{R}_B \right] \begin{bmatrix} \bar{\boldsymbol{\alpha}}_{BU} \\ \Delta \bar{\mathbf{p}}_{BU} \\ \bar{\boldsymbol{\alpha}}_B \\ \Delta \bar{\mathbf{p}}_B \end{bmatrix}
 \end{aligned}$$

Russell H. Taylor Copyright 1996-2022; 600.455/655 lecture notes

JHU Laboratory for Computational Sensing and Robotics



114

## Parametric Sensitivity

Suppose you have an explicit formula like

$$\bar{\mathbf{p}}_3 = \begin{bmatrix} L_1 \cos(\theta_1) + L_2 \cos(\theta_1 + \theta_2) + L_3 \cos(\theta_1 + \theta_2 + \theta_3) \\ L_1 \sin(\theta_1) + L_2 \sin(\theta_1 + \theta_2) + L_3 \sin(\theta_1 + \theta_2 + \theta_3) \\ 0 \end{bmatrix}$$

and know that the only variation is in parameters like  $L_k$  and  $\theta_k$ . Then you can estimate the variation in  $\bar{\mathbf{p}}_3$  as a function of variation in  $L_k$  and  $\theta_k$  by remembering your calculus.

$$\Delta \bar{\mathbf{p}}_3 \cong \begin{bmatrix} \frac{\partial \bar{\mathbf{p}}_3}{\partial \bar{L}} & \frac{\partial \bar{\mathbf{p}}_3}{\partial \bar{\theta}} \end{bmatrix} \begin{bmatrix} \Delta \bar{L} \\ \Delta \bar{\theta} \end{bmatrix}$$



## Parametric Sensitivity

Grinding this out gives:

$$\Delta \bar{\mathbf{p}}_3 \cong \begin{bmatrix} \frac{\partial \bar{\mathbf{p}}_3}{\partial \bar{L}} & \frac{\partial \bar{\mathbf{p}}_3}{\partial \bar{\theta}} \end{bmatrix} \begin{bmatrix} \Delta \bar{L} \\ \Delta \bar{\theta} \end{bmatrix}$$

where

$$\bar{L} = [L_1, L_2, L_3]^T$$

$$\bar{\theta} = [\theta_1, \theta_2, \theta_3]^T$$

$$\frac{\partial \bar{\mathbf{p}}_3}{\partial \bar{L}} = \begin{bmatrix} \cos(\theta_1) & \cos(\theta_1 + \theta_2) & \cos(\theta_1 + \theta_2 + \theta_3) \\ \sin(\theta_1) & \sin(\theta_1 + \theta_2) & \sin(\theta_1 + \theta_2 + \theta_3) \\ 0 & 0 & 0 \end{bmatrix}$$

$$\frac{\partial \bar{\mathbf{p}}_3}{\partial \bar{\theta}} = \begin{bmatrix} -L_1 \sin(\theta_1) - L_2 \sin(\theta_1 + \theta_2) - L_3 \sin(\theta_1 + \theta_2 + \theta_3) & -L_2 \sin(\theta_1 + \theta_2) - L_3 \sin(\theta_1 + \theta_2 + \theta_3) & -L_3 \sin(\theta_1 + \theta_2 + \theta_3) \\ L_1 \cos(\theta_1) + L_2 \cos(\theta_1 + \theta_2) + L_3 \cos(\theta_1 + \theta_2 + \theta_3) & L_2 \cos(\theta_1 + \theta_2) + L_3 \cos(\theta_1 + \theta_2 + \theta_3) & L_3 \cos(\theta_1 + \theta_2 + \theta_3) \\ 0 & 0 & 0 \end{bmatrix}$$



## More generally ...

Suppose that we have a vector function

$$\bar{\mathbf{v}} = \bar{\mathbf{g}}(\bar{\mathbf{q}}) = [g_1(\bar{\mathbf{q}}), \dots, g_m(\bar{\mathbf{q}})]^T$$

of parameters  $\bar{\mathbf{q}} = [q_1, \dots, q_n]$ . Then we can estimate the value of

$$\bar{\mathbf{v}} + \Delta\bar{\mathbf{v}} = \bar{\mathbf{g}}(\bar{\mathbf{q}} + \Delta\bar{\mathbf{q}})$$

by

$$\bar{\mathbf{v}} + \Delta\bar{\mathbf{v}} \approx \bar{\mathbf{g}}(\bar{\mathbf{q}}) + \mathbf{J}_g(\bar{\mathbf{q}}) \bullet \Delta\bar{\mathbf{q}}$$

where

$$\mathbf{J}_g(\bar{\mathbf{q}}) = \begin{bmatrix} \frac{\partial g_1}{\partial q_1} & \frac{\partial g_1}{\partial q_j} & \frac{\partial g_1}{\partial q_n} \\ \vdots & \vdots & \vdots \\ \frac{\partial g_j}{\partial q_1} & \dots & \frac{\partial g_j}{\partial q_j} & \dots & \frac{\partial g_j}{\partial q_n} \\ \vdots & \vdots & \vdots & \vdots & \vdots \\ \frac{\partial g_m}{\partial q_1} & \frac{\partial g_m}{\partial q_j} & \frac{\partial g_m}{\partial q_n} \end{bmatrix}$$

