



NSF Engineering Research Center
for Computer Integrated Surgical
Systems and Technology



Segmentation and Modeling

CIS I – 600.455/655

Russell H. Taylor

John C. Malone Professor of Computer Science,
with joint appointments in Mechanical Engineering, Radiology & Surgery
Director, Laboratory for Computational Sensing and Robotics
The Johns Hopkins University
rht@jhu.edu

Note: This lecture contains many slides from colleagues,
including Jerry Prince, Eric Grimson, and Ayushi Sinha.

I have tried to make appropriate acknowledgments on
the sides



WHITING
SCHOOL OF
ENGINEERING
THE JOHNS HOPKINS UNIVERSITY



1

Segmentation & Modeling




FIGURE 4.2 Here we represent the surface once we have reached a minimum of the energy E . Some vertical and horizontal cross-sections of the surface are given. They show an accurate localization of the surface at the edge points.




FIGURE 4.3 A 3D representation of the surface depicted in figure 4.2.


Images

Segmented
Images


Models




2



3



4




Brain Examples: Blake Lucas




Image Segmentation

- Process of identifying structure in 2D & 3D images
- Output may be
 - labeled pixels
 - edge map
 - set of contours




 **Manual Segmentation
(Outlining)**



- Extremely time-consuming (~6 hours per case)
- 3D Imagery – Performed slice at a time
- Some structures near impossible (blood vessels)


10/19/07 10/79

Copyright © 1999-2023 R. H. Taylor Credit: Eric Grimson
Computer Integrated Surgery 600.455/655 

7

Automation Approaches

- Pixel-based
 - Thresholding
 - Region growing
 - Machine learning approaches
- Edge/Boundary based
 - Contours/boundary surface
 - Deformable warping
 - Deformable registration to atlases

Copyright © 1999-2023 R. H. Taylor Computer Integrated Surgery 600.455/655 

8

Thresholding

3	5	7	3	4	2	1
2	4	9	10	22	9	3
3	5	12	11	15	10	3
5	6	11	9	17	19	1
2	3	11	12	18	16	2
3	6	8	10	18	9	5
4	6	7	8	3	3	1



Thresholding

3	5	7	3	4	2	1
2	4	9	10	22	9	3
3	5	12	11	15	10	3
5	6	11	9	17	19	1
2	3	11	12	18	16	2
3	6	8	10	18	9	5
4	6	7	8	3	3	1



Thresholding

3	5	7	3	4	2	1
2	4	9	10	22	9	3
3	5	12	11	15	10	3
5	6	11	9	17	19	1
2	3	11	12	18	16	2
3	6	8	10	18	9	5
4	6	7	8	3	3	1

Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



11

Thresholding

3	5	7	3	4	2	1
2	4	9	10	22	9	3
3	5	12	11	15	10	3
5	6	11	9	17	19	1
2	3	11	12	18	16	2
3	6	8	10	18	9	5
4	6	7	8	3	3	1


Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



12

“Partial volume” effects



Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



13

“Partial volume” effects

			80	60	90	100	100	
100	100	100	90	55	60	100	100	
	100	100	55	0	40	100		
		100	60	0	70	100		
		60	50	45	100	98		


Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



14

“Partial volume” effects




Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



15

“Partial volume” effects




Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



16

“Partial volume” effects



Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655





17



Segment statistically

- Measure distribution of intensities at known tissue locations
- Use nearest neighbor style classifiers for all other voxels




Credit: Eric Grimson

Copyright © 1999-2023 R. H. Taylor


Computer Integrated Surgery 600.455/655




23

 **CSAIL**


Standard Scans




10/19/07 13/79

Copyright © 1999-2023 R. H. Taylor Credit: Eric Grimson
Computer Integrated Surgery 600.455/655 


24

 **CSAIL**

Statistical segmentation



10/19/07 14/79

Copyright © 1999-2023 R. H. Taylor Credit: Eric Grimson
Computer Integrated Surgery 600.455/655 

25



Between Scylla and Charybdis

- Problem: imagery contains non-linear gain artifacts that shift the intensity values in a non-stationary way
- If one knew the gain field, could correct image and use standard statistical method
- If one knew the tissue types, could predict the image and find the gain field correction
- Solution: Use Expectation/Maximization method to iteratively solve for gain field and tissue class, using probabilistic models

10/19/07

15/79

Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655

Credit: Eric Grimson



26



EM-Segmentation [Wells 1994]

E-Step

Compute tissue posteriors using current intensity correction.



Estimate intensity correction using residuals based on current posteriors.



M-Step

10/19/07

16/79


Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655


Credit: Eric Grimson




27

 **CSAIL**


Standard Scans




10/19/07 13/79

Copyright © 1999-2023 R. H. Taylor Credit: Eric Grimson
Computer Integrated Surgery 600.455/655 


28

 **CSAIL**


Statistical segmentation



10/19/07 18/79


Copyright © 1999-2023 R. H. Taylor Credit: Eric Grimson
Computer Integrated Surgery 600.455/655 

29



CSAIL


Gain Corrected Scans



10/19/07
19/79

Copyright © 1999-2023 R. H. Taylor

Credit: Eric Grimson
Computer Integrated Surgery 600.455/655




30

Deformable Surfaces

3	5	7	3	4	2	1
2	4	9	10	22	9	3
3	5	12	11	15	10	3
5	6	11	9	17	19	1
2	3	11	12	18	16	2
3	6	8	10	18	9	5
4	6	7	8	3	3	1


Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



31

Deformable Surfaces



Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



32

Deformable Surfaces

A 7x7 grid of numbers is centered on the page. The grid is surrounded by a pink shaded, irregular shape that roughly follows the outline of the grid. The numbers in the grid are:

3	5	7	3	4	2	1
2	4	9	10	22	9	3
3	5	12	11	15	10	3
5	6	11	9	17	19	1
2	3	11	12	18	16	2
3	6	8	10	18	9	5
4	6	7	8	3	3	1

Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



33

Deformable Surfaces

3	5	7	3	4	2	1
2	4	9	10	22	9	3
3	5	12	11	15	10	3
5	6	11	9	17	19	1
2	3	11	12	18	16	2
3	6	8	10	18	9	5
4	6	7	8	3	3	1

- Basic concepts proposed by Demetri Terzopoulos
 - M. Kass, A. Witkin, and D. Terzopoulos, "Snakes:Active Contour Models", *Intl Journal of Computer Vision*, pp. 321-331, 1988.
- Many refinements since then

Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



34

Traditional Active Contour


- Initialize a curve $\mathbf{X}(s)$ around or near the object boundary
- Find $\mathbf{X}(s)$ that minimizes:

$$E = \int_0^1 \left[\frac{1}{2} \{ \alpha |\mathbf{X}'(s)|^2 + \beta |\mathbf{X}''(s)|^2 \} + E_{\text{ext}} \{ \mathbf{X}(s) \} \right] ds$$

- Where $\alpha = 0.001$, $\beta = 0.09$
and

$$E_{\text{ext}}(x, y) = -\|\nabla f(x, y)\|^2$$

- How to find $\mathbf{X}(s)$?



Copyright © 1999-2023 R. H. Taylor



© Jerry L. Prince

Computer Integrated Surgery 600.455/655



35

Dynamic Equation From E-L Equation

- Euler-Lagrange equation

$$\frac{\partial}{\partial s} \left(\alpha \frac{\partial \mathbf{X}}{\partial s} \right) - \frac{\partial^2}{\partial s^2} \left(\beta \frac{\partial^2 \mathbf{X}}{\partial s^2} \right) - \nabla P(\mathbf{X}) = 0$$

- Make \mathbf{X} dynamic: $X(s) \rightarrow X(s, t)$

$$\mathbf{X}(s, t) = [X(s, t), Y(s, t)]$$

where $s \in [0, 1]$

- Now set “in motion” – gradient descent

$$\gamma \frac{\partial \mathbf{X}}{\partial t} = \frac{\partial}{\partial s} \left(\alpha \frac{\partial \mathbf{X}}{\partial s} \right) - \frac{\partial^2}{\partial s^2} \left(\beta \frac{\partial^2 \mathbf{X}}{\partial s^2} \right) - \nabla P(\mathbf{X})$$

- General dynamical equation for snake:

$$\gamma \mathbf{X}_t = \mathbf{F}_{\text{int}} + \mathbf{F}_{\text{ext}}$$

Copyright © 1999-2023 R. H. Taylor




© Jerry L. Prince

Computer Integrated Surgery 600.455/655



36


Example: Bone Modeling from CT




38


Bone Structure

- Compact bone
- Spongy bone
- Medullary Cavity



Bone Structure







Copyright © 1999-2023 R. H. Taylor Credit: Yao and Taylor
Computer Integrated Surgery 600.455/655

39

Bone Contour Extraction



Needle graph of Image force




Bone Contours

Copyright © 1999-2023 R. H. Taylor Credit: Yao and Taylor
Computer Integrated Surgery 600.455/655

41

Bone Contour Extraction Closer-up view



Needle graph of Image force



Bone Contours


Copyright © 1999-2023 R. H. Taylor

Credit: Yao and Taylor
Computer Integrated Surgery 600.455/655

42

3D Deformable Surface Model

Commonly done with triangle mesh



- Added complexity, time, especially to avoid self-intersection

Copyright © 1999-2023 R. H. Taylor

© Jerry L. Prince

Computer Integrated Surgery 600.455/655

43


Critique of Parametric Models

- Advantages:
 - explicit equations, direct implementation
 - automatic topology control
- Disadvantages:
 - costly to prevent overlaps
 - requires reparameterization to space out triangles




Basic Idea of Geometric Active Contours

$\mathbf{X}(s, t)$ The parametric curve



$\phi(x, t)$ A level set function




- The level set function is usually a signed distance function
- Convention:
 - positive on outside
 - negative on inside

$\{\mathbf{x} \mid \phi(\mathbf{x}, t) = 0\}$ The zero level set



GDM: Geometric Deformable Model

- Conventional level set function $\phi(x,t)$
 - signed distance function
- Change the values of $\phi \rightarrow$ move the contour



Copyright © 1999-2023 R. H. Taylor



© Jerry L. Prince

Computer Integrated Surgery 600.455/655



46

Philosophy of GDMs

- Curve is not parameterized until the end of evolution
 - tangential forces are meaningless
 - forces must be derived from “spatial position” and “time” because location on the curve is meaningless
 - Final contour is an “isocurve” (2D) or “isosurface” (3D)
 - It has a “Eulerian” rather than “Lagrangian” framework
- Speed function incorporates internal and external forces
 - Design of geometric model is accomplished by selection of $F(x)$, the speed function
 - curvature terms takes the place of internal forces
- “Action” is near the zero level set
 - “narrowband” methods are computationally more efficient

Copyright © 1999-2023 R. H. Taylor



© Jerry L. Prince

Computer Integrated Surgery 600.455/655



47

Ventricle Segmentation



Copyright © 1999-2023 R. H. Taylor



© Jerry L. Prince

Computer Integrated Surgery 600.455/655



50

Cortical Surface Segmentation



Copyright © 1999-2023 R. H. Taylor



© Jerry L. Prince

Computer Integrated Surgery 600.455/655



51

Critique of Geometric Deformable Models


- Advantages:
 - Produce closed, non-self-intersecting contours
 - Independent of contour parameterization
 - Easy to implement: numerical solution of PDEs on regular computational grid
 - Stable computations
- Disadvantages:
 - topologically flexible
 - some numerical difficulties with narrowband and level set function reinitialization




Topology Preservation Principle

- Preserving topology is equivalent to maintaining the topology of the digital object
- The digital object can only change topology when the level set function changes sign at a grid point
- To prevent the digital object from changing topology, the level set function should only be allowed to change sign at *simple* points
 - **Definition:** a point is simple if adding or removing the point from a binary object will not change the digital object's topology





54



55

Topology Preserving Geometric Deformable Model (TGDM)

- Evolve level set function according to GDM PDE
- If level set function is going to change sign, check whether the point is a simple point
 - If simple, permit the sign-change
 - If not simple, prohibit the sign-change
 - (replace the grid value by epsilon with same sign)
 - (Roughly, this step adds 7% computation time.)
- Extract the final contour using a *connectivity consistent isocontour algorithm*


X. Han, C. Xu, and J. L. Prince, "A topology preserving level set method for geometric deformable models", IEEE Transactions on Pattern Analysis and Machine Intelligence, vol. 25- 6, pp. 755-768, 2003.



56

3D Digital Connectivity


- In 3D there are three connectivities: 6, 18, and 26
- Four consistent connectivity pairs:
(foreground, background) \rightarrow (6,18), (6,26), (18,6), (26,6)



57

Simple Point


- **Definition:** a point is simple if adding or removing the point from a binary object will not change the digital object's topology
- **Determination:** can be characterized locally by the configuration of its neighborhood (8- in 2D, 26- in 3D) [Bertrand & Malandain 1994]



© Jerry L. Prince

58

Nested Deformable Surfaces



Copyright © 1999-2023 R. H. Taylor


© Jerry L. Prince

Computer Integrated Surgery 600.455/655

59

TGDM for Inner Surface

[Han et al., NeuroImage, 2004]



Initial WM Isosurface



Evolving GM/WM Interface

$$\Phi_t = (\omega_1 R(\bar{x}) + \omega_2 \kappa(\bar{x})) \|\nabla \Phi\|$$

Copyright © 1999-2023 R. H. Taylor




© Jerry L. Prince

Computer Integrated Surgery 600.455/655



60

TGDM for Central Surface



Initialize with GM/WM surface



Evolving toward Central Surface

$$\Phi_t = (\omega_1 R(\bar{x}) + \omega_2 \kappa(\bar{x})) \|\nabla \Phi\| + \omega_3 F_{GVF}(\bar{x}) \cdot \nabla \Phi$$

Copyright © 1999-2023 R. H. Taylor




© Jerry L. Prince

Computer Integrated Surgery 600.455/655



61

TGDM for Outer Surface



Start from Central Surface

Evolving toward Outer Surface

$$\Phi_t = (\omega_1 R(\bar{x}) + \omega_2 \kappa(\bar{x})) \|\nabla \Phi\| + \omega_3 F_{GVF}(\bar{x}) \cdot \nabla \Phi$$

Copyright © 1999-2023 R. H. Taylor



© Jerry L. Prince


Computer Integrated Surgery 600.455/655



62



Segmenting with Spatial Priors



- Given standard scan, and probability maps of tissue types
- Elastically register standard scan to new case
- Apply transformation to all probability maps
- Use as prior probabilities in EM-MF segmentation
- Apply in hierarchical manner (first segment out major structures, then substructures)

10/19/07

26/79

Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655


Credit: Eric Grimson



63

Example: Sinuses & Nasal Airway

Complex structures with thin boundaries



[3] Kainz, J. and Stammberger, H., "The roof of the anterior ethmoid: A place of least resistance in the skull base," American Journal of Rhinology 3(4), 191-199 (1989).
 [4] Tao, H., Ma, Z., Dai, P., and Jiang, L., "Computer-aided three-dimensional reconstruction and measurement of the optic canal and intracanalicular structures," The Laryngoscope 109(9), 1499-1502 (1999).

Copyright © 1999-2023 R. H. Taylor


Slide Credit: Ayushi Sinha

Computer Integrated Surgery 600.455/655



64

Automated Segmentation Workflow



A. Sinha, S. Leonard, A. Reiter, M. Ishii, R. H. Taylor, and G. D. Hager, "Automatic segmentation and statistical shape modeling of the paranasal sinuses to estimate natural variations", in Proc. SPIE 9784, San Diego, Feb. 27, 2016. pp. 97840D.1-8.


Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



65

Template Creation



BB Avants, P Yushkevich, J Pluta, D Minko, M Korczykowski, J Detre, JC Gee, "The optimal template effect in hippocampus studies of diseased populations," *NeuroImage* 49(3), p. 2457, 2010.

Copyright © 1999-2023 R. H. Taylor


Slide Credit: Ayushi Sinha

Computer Integrated Surgery 600.455/655



66

Deformable Registration of Template to Image



BB Avants, NJ Tustison, . Song, PA Cook, A Klein, and JC Gee, "A reproducible evaluation of ANTs similarity metric performance in brain image registration," *NeuroImage* 54(3), pp. 2033-2044, 2011.

Copyright © 1999-2023 R. H. Taylor


Slide Credit: Ayushi Sinha

Computer Integrated Surgery 600.455/655



67

Adjustment of Template to Patient CT



[10] C. Xu and J. L. Prince, "Gradient vector flow: A new external force for snakes," in IEEE Computer Vision and Pattern Recognition, pp. 66-71, 1997.
[11] C. Xu and J. Prince, "Snakes, shapes, and gradient vector flow," IEEE Transactions on Image Processing, 7, pp. 359-369, March 1998.

Copyright © 1999-2023 R. H. Taylor


Slide Credit: Ayushi Sinha

Computer Integrated Surgery 600.455/655



68

Results



A. Sinha, A. Reiter, S. Leonard, M. Ishii, G. D. Hager, and R. H. Taylor, "Simultaneous segmentation and correspondence improvement using statistical modes", in SPIE Medical Imaging, Orlando, 2017.


Copyright © 1999-2023 R. H. Taylor

Slide Credit: Ayushi Sinha


Computer Integrated Surgery 600.455/655



69





70



71

Example: Deep Learning in Multi-Modality Segmentation



This paper has been published in October 2016 as: Moeskops, P., Wolterink, J.M., van der Velden, B.H.M., Gilhuijs, K.G.A., Leiner, T., Viergever, M.A., and Išgum, I. (2016). Deep learning for multi-task medical image segmentation in multiple modalities. In: Medical Image Computing and Computer-Assisted Intervention – MICCAI, 2016, Part II, LNCS 9901, pp. 478-486


Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



72

Automated Segmentation of Temporal Bone Structures



Andy Ding, Alex Lu, Francis Creighton, Russ Taylor

Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



73

Modeling

- Representation of anatomical structures
- Models can be
 - Images
 - Labeled images
 - Boundary representations



FROM VOXELS TO SURFACES

Representing solids:

- B-REP - surface representation,
d/s of vertices, edges, faces.
- CSG- composition of primitive solids

binary image → **B-REP representation**

Surface construction algorithms:

- 2D-based algorithms
- 3D-based algorithms



Surface Representations

- Implicit Representations
 $\{\bar{x} \mid f(\bar{x}) = 0\}$
- Explicit Representations
 - Polyhedra
 - Interpolated patches
 - Spline surfaces
 - ...




FIGURE 4.7 Segmentation of vertebra defined by a set of CT slices. Four steps of the deformation of a roughly spherical snake spline toward the vertebra are shown.

Source: CIS p 73 (Lavallee image)




Polyhedral Boundary Reps

- Common in computer graphics
- Many data structures.
 - FEV lists
 - Winged edge
 - Connected triangles
 - etc.



FEV lists

- Explicit linked lists of faces, edges, vertices
- Many variations
- Key properties
 - Convenient to traverse
 - Lists are variable length
 - Can be tricky to maintain consistency



Copyright © 1999-2023 R. H. Taylor


Computer Integrated Surgery 600.455/655



79

Winged Edge

- Baumgart 1974
- Basic data structures
 - winged edge (topology)
 - vertex (geometry)
 - face (surfaces)
- Key properties
 - constant element size
 - topological consistency




Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



80



81

Connected Triangles

- Basic data structures
 - Triangle (topology, surfaces)
 - Vertex (geometry)
- Properties
 - Constant size elements
 - Topological consistency

Copyright © 1999-2023 R. H. Taylor Computer Integrated Surgery 600.455/655

82

Anatomy of a Springl

Blake Lucas

2D Iso-Surface Springl

2D

3D

3D

Slide credit: Blake Lucas' PhD Thesis Defense, 2012
Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655

83

Deformable Surfaces & Level Sets

Blake Lucas – “Springls” (October 2010)


Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655

84

Tetrahedral Mesh Data Structure

- Vertex list
 - x, y, z coordinates
 - reference to one tetrahedron
- Tetrahedron list
 - references to four vertices
 - references to four face neighbors
- Properties such as density functions



Credit: Yao and Taylor

Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



85

Advantages of Tetrahedral Mesh

- Greatest degree of flexibility
- Data structure, data traversal, and data rendering are more involved
- Ability to better adapt to local structures
- Computational steps such as interpolation, integration, and differentiation can be done in closed form
- Finite element analysis
- Hierarchical structure of multiple resolution meshes

Credit: Yao and Taylor

Copyright © 1999-2023 R. H. Taylor


Computer Integrated Surgery 600.455/655



86

2D-based Methods for Shape Reconstruction

- Treat 3D volume as a stack of slices
- Outline
 - Find contours in each 2D slice
 - Match contours in successive slices
 - Connect contours to create tiled surfaces (for boundary representation)
 - Use contours to guide subdivision of space between slices into tetrahedra (for volumes)



Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655




89

SURFACE CONSTRUCTION ALGORITHMS

2D-based algorithms

1. 2D contour extraction
2. tiling of contours

Keppel (1975), Fuchs (1978), Christiansen (1981), Shantz (1981), Ganapathy (1982), Cook (1983), Zyda (1987), Boissonnat (1988), Schwartz (1988)



Contour extraction


- Sequential scanning
- boundary following (random access to pixels)

Copyright © 1999-2023 R. H. Taylor


Computer Integrated Surgery 600.455/655



90



91



92

Tetrahedral Mesh Tiling


- Objectives
 - Subdivide the space between adjacent slices into tetrahedra, slice by slice
- Method
 - Two-steps tiling strategy
 - 2D tiling and medial axis tiling
 - 3D tiling

Copyright © 1999-2023 R. H. Taylor

Credit: Yao and Taylor
Computer Integrated Surgery 600.455/655

93

Tiling Strategy




Copyright © 1999-2023 R. H. Taylor

Credit: Yao and Taylor
Computer Integrated Surgery 600.455/655

94

Tiling Constraints

- Non-intersection between tetrahedra
- Continuity between slices
- Continuity between layers




Copyright © 1999-2023 R. H. Taylor

Credit: Yao and Taylor
Computer Integrated Surgery 600.455/655

95

Correspondence Problem

- Examining the overlap and distance between contours on adjacent slices
- Graph based method




Copyright © 1999-2023 R. H. Taylor

Credit: Yao and Taylor
Computer Integrated Surgery 600.455/655


96

Branching Problem

- Branching Between layers
 - Convert to tiling of 3 contours
- Branching Between contours
 - Composite contour
 - Split contour



Split Contour



Composite Contour

Copyright © 1999-2023 R. H. Taylor

Credit: Yao and Taylor
Computer Integrated Surgery 600.455/655

97

Metric Functions

- Maximize Volume, f_v
- Minimize Area, f_a
- Minimize Density Deviation, f_d
- Minimize Span Length, f_s

Current Metric Function:

- Combination of minimizing density deviation and span length
- Minimize $F = w_1 * f_d + w_2 * f_s$


Copyright © 1999-2023 R. H. Taylor

Credit: Yao and Taylor
Computer Integrated Surgery 600.455/655

98

3D-based methods for Surface Reconstruction

- Segment image into labeled voxels
- Define surface and connectivity structure
- Can treat boundary element between voxels as a face or a vertex



Copyright © 1999-2023 R. H. Taylor


Computer Integrated Surgery 600.455/655



99

3D-BASED ALGORITHMS

Block-form and Beveled-form representations of surface:



Copyright © 1999-2023 R. H. Taylor


Computer Integrated Surgery 600.455/655



100

Block form methods

- “Cuberille”-type methods
- Treat voxels as little cubes
- May produce self-intersecting volumes
- E.g., Herman, Udupa




Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



101



Ref: Udupa , CIS Book, p47

FIGURE 3.3 Renditions of the first scene by robust structure-rendering methods: (a) R1, (b) R2, (c) R3, (d) R4, (e) R5.

Copyright © 1999-2023 R. H. Taylor


455/655



102

Beveled form methods

- “Marching cubes” type
- Voxels viewed as 3D grid points
- Vertices are points on line between adjacent grid points
- E.g. Lorensen&Cline, Baker, Kalvin, many others



Copyright © 1999-2023 R. H. Taylor


Computer Integrated Surgery 600.455/655



103

Block form to beveled form

Segmented voxels



Copyright © 1999-2023 R. H. Taylor


Computer Integrated Surgery 600.455/655



104

Block form to beveled form

Duality between voxels and vertices on adjacency graph



Copyright © 1999-2023 R. H. Taylor


Computer Integrated Surgery 600.455/655



105

Block form to beveled form

Label vertices based on segmentation labels



Copyright © 1999-2023 R. H. Taylor


Computer Integrated Surgery 600.455/655



106

Block form to beveled form

Boundary crosses edges between occupied and empty vertices



Note: Choice of exact vertex placement is somewhat arbitrary. One choice is linear interpolation along edge based on density.

Copyright © 1999-2023 R. H. Taylor


Computer Integrated Surgery 600.455/655



109

Beveled form basic approach

- Segment the 3D volume
- Scan 3D volume to process “8-cells” sequentially
- Use labels of 8 cells as index in (256 element) lookup table to determine where surfaces pass thru cell
- Connect up topology
- Use various methods to resolve ambiguities



Source: Kalvin survey

Copyright © 1999-2023 R. H. Taylor


Computer Integrated Surgery 600.455/655



111

Marching Cubes Isosurface Algorithm

- How to “tile/triangulate” the zero level set?
- Consider values on corners of voxel (cube)
- Label as
 - above isovalue
 - below isovalue
- Determine the position of a triangular mesh surface passing through the voxel
 - Linear interpolation



Copyright © 1999-2023 R. H. Taylor

  © Jerry L. Prince

Computer Integrated Surgery 600.455/655





112

Connectivity Errors

Most isosurface codes use rules that lead to connectivity errors

- Multiple meshes
 - typically solved by selecting the largest mesh
- Touching vertices, edges, and faces
 - typically solved isovalue choice
- Ambiguous faces and cubes
 - solved by use of a specially coded *connectivity consistent* MC algorithm

Copyright © 1999-2023 R. H. Taylor

  © Jerry L. Prince



Computer Integrated Surgery 600.455/655



113

Ambiguous Faces



Two possible tilings:

Copyright © 1999-2023 R. H. Taylor  © Jerry L. Prince Computer Integrated Surgery 600.455/655 

115

Ambiguous Cubes

Two possible tilings:

Copyright © 1999-2023 R. H. Taylor  © Jerry L. Prince Computer Integrated Surgery 600.455/655 

116

Wyvill, McPheters, Wyvill

Step 1: determine edges on each face of 8 cube





Figure 6: The seven cases for calculating vertices and edges

Step 2: Connect the edges up to make surfaces



Ambiguities

- Arise when alternate corners of a 4-face have different labels
- Ways to resolve:
 - supersampling
 - look at adjacent cells
 - tetrahedral tessellation



Tetrahedral Tesselation

- Many Authors
- Divide each 8-cube into tetrahedra
- Connect tetrahedra
- No ambiguities




Figure 8: The two tetrahedral partitionings of an 8-cell.




Figure 9: The two cases used for surface construction.


Beveled-form algorithms based on the tetrahedral decomposition of the 3D volume have been developed Payne and Toga [34], Hall and Warren [21], and Nielson *et al.* [29]. While this approach does provide a neat resolution to the ambiguous 8-cell problem, it

Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



120




Copyright © 1999-2023 R. H. Taylor

Source: C. Cutting, CIS Book


Computer Integrated Surgery 600.455/655



124



125




126

Classic Laplacian Smoothing Method

- Equation

$$v'_i = \frac{1}{|N_i|} \sum_{j \in N_i} v_j$$



- Advantages
 - Fast and easy
- Drawbacks
 - Shrinkage
 - Invalid elements

Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655




127

Enhanced Laplacian Smoothing Method

- Objective
 - Reduce shrinkage
- Method
 - Project back to boundary

$$v'_i = \text{proj} \left(\frac{1}{|N_i|} \sum_{j \in N_i} v_j \right)$$




Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



128

Average and reproject




Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



129

Average and reproject



Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655




130

Enhanced Laplacian Smoothing Method


- Objective
 - Prevent invalid element
- Method
 - Iterative assignment

$$v_i^{(0)} = \text{proj}\left(\frac{1}{|N_i|} \sum_{j \in N_i} v_j\right)$$

$$v_i^{(k)} = \alpha \cdot v_i + (1 - \alpha)v_i^{(k-1)}, 0 \leq \alpha \leq 1$$



Classic Laplacian



Enhanced Laplacian


Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



131

Mesh Smoothing Results



a) Before Smoothing

b) After Smoothing


Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



132

Tetrahedral Mesh Models



Model	Num of Vertices	Num of Tetrahedra	Num of Slices	Total Num of Voxels inside	Avg Num of voxels Per Tetra	Volume (mm ³)	Avg Vol. Per Tetra (mm ³)
Femur	6163	31,537	83	1,802,978	57.1	312,107	9.9
Pelvis	8219	32,741	110	1,941,998	59.3	347,070	10.6


Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



133

Example: Bone Modeling from CT



Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



134

Density Functions

- n-degree Bernstein polynomial in barycentric coordinate

$$D(\mu) = \sum_{i+j+k+l=n}^n C_{i,j,k,l} B_{i,j,k,l}^n(\mu)$$

$C_{i,j,k,l}$ polynomial coefficient

$$B_{i,j,k,l}^n(\mu) = \frac{n!}{i!j!k!l!} \mu_x^i \mu_y^j \mu_z^k \mu_w^l \text{ barycentric Bernstein basis}$$



Barycentric Coordinate of Tetrahedron

- Local coordinate system
- Symmetric and normalized
- Every 3D position can be defined by an unique coordinate (x, y, z, w)

$$V = x*V_a + y*V_b + z*V_c + w*V_d$$

$x+y+z+w=1$, V_a, V_b, V_c, V_d are coordinate of Tetrahedron vertices

x,y,z,w within $[0,1]$ if V is inside the tetrahedron



Density Functions

- Advantages
 - Efficient in storage
 - Continuous function
 - Explicit form
 - Convenient to integrate, to differentiate, and to interpolate



Fitting Density Function

- Minimize the density difference between the density function and CT data set

$$\min \sum_{\rho_i \in \Omega} \left(\left(\sum_{i+j+k+l=n} C_{i,j,k,l} B_{i,j,k,l}^n(\mu_{\rho_i}) \right) - T(\mu_{\rho_i}) \right)^2$$

Ω is the set of sample voxels,
 $T(\mu_{\rho_i})$ is the density value from the CT data set.


$$\begin{bmatrix} B_1(\mu_{\rho_1}) & B_2(\mu_{\rho_1}) & \dots & B_m(\mu_{\rho_1}) \\ B_1(\mu_{\rho_2}) & B_2(\mu_{\rho_2}) & \dots & B_m(\mu_{\rho_2}) \\ \vdots & \vdots & \vdots & \vdots \\ B_1(\mu_{\rho_s}) & B_2(\mu_{\rho_s}) & \dots & B_m(\mu_{\rho_s}) \end{bmatrix} \begin{bmatrix} C_1 \\ C_2 \\ \vdots \\ C_m \end{bmatrix} = \begin{bmatrix} T(\mu_{\rho_1}) \\ T(\mu_{\rho_2}) \\ \vdots \\ T(\mu_{\rho_s}) \end{bmatrix}$$

s : number of sample voxels
 m : number of density function coefficient,
 $s > 2m$




Accuracy vs Degree of Density Function

- Use CT data set as ground truth
- Cut an arbitrary plane through the model



Arbitrary Cutting Plane



Partitions by tetrahedra on cutting plane


Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



139

Accuracy vs Degree of Density Function (cont')



Ground Truth

n=0

n=1

n=2

n=3

n=4


Degree	0	1	2	3	4	5	6	7	8
Coeff Number	1	4	10	20	35	56	84	120	165
Avg. Density Err (%)	3.291	1.583	0.766	0.442	0.298	0.216	0.167	0.149	0.128

Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655




140



141

Model Simplification

- Models used in CIS must be guaranteed to be accurate within known bounds
- But 3D models from medical images often are very complex, and require representations with large data structures.
- Algorithms using models are often computationally expensive, and computation costs go up with model complexity
- **PROBLEM:** reduce model complexity while preserving adequate accuracy



~350,000 triangles!

Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655

142

Model simplification

- Problem is also common in computer graphics
 - There is a growing literature
 - **But** many graphics techniques only care about appearance, and do not necessarily preserve accuracy or other properties (like topological connectivity) important for computational analysis
- Broadly, two classes of approaches
 - Top down
 - Bottom-up



Top down

- Active surfaces used in segmentation
- Deformable registration of an atlas to a patient
 - E.g., skull atlas discussed in craniofacial lecture had about 5000 polygons (perhaps 15-20,000 triangles)
- Recursive approximations
 - E.g., Pizer *et al.* “cores”



Bottom up methods

- Typically, start with very high detail model generated from CT images
 - Large number of elements a consequence of small size of pixels & way model is created
- Then merge nearby elements into larger elements
 - E.g., “decimation” (Lorenson, et. al.)
 - E.g., “superfaces” (Kalvin & Taylor)
 - E.g., Gueziec
- An excellent tutorial may be found in:
 - David Luebke; A Developer’s Survey of Polygonal Simplification Algorithms; IEEE Computer Graphics and Application, May 2001


Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



145

Bottom-up merging



Source: David Luebke; A Developer’s Survey of Polygonal Simplification Algorithms; IEEE Computer Graphics and Application, May 2001

Copyright © 1999-2023 R. H. Taylor

Computer Integrated Surgery 600.455/655



146